

# NORTH DAKOTA

## DEPARTMENT OF TRANSPORTATION

HEN-3-999(059)

## Benson and Ramsey Counties

ND 57/20 - US 281 to CR 1



## Signing, Pavement Marking, Dynamic Message Sign

### Vision Zero Safety Corridor

|  |       |                |       |             |           |
|--|-------|----------------|-------|-------------|-----------|
|  | STATE | PROJECT NO.    | PCN   | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 24035 | 1           | 1         |

|                                 |   |
|---------------------------------|---|
| <b>GOVERNING SPECIFICATIONS</b> | Date Published and Adopted<br>by the North Dakota<br>Department of Transportation |
| Standard Specifications         | 7/1/2024  |
| Supplemental Specifications     | NONE  |

| <u>PROJECT NUMBER \ DESCRIPTION</u> | <u>NET MILES</u> | <u>GROSS MILES</u> |
|-------------------------------------|------------------|--------------------|
| HEN-3-999(059)                      |                  | 17.568             |




STATE COUNTY MAP

|                              |
|------------------------------|
| DESIGNER<br>Jaycee Allery    |
| DESIGNER<br>Spencer Ulvestad |
| DESIGNER                     |

ND DEPARTMENT OF TRANSPORTATION  
OFFICE OF PROJECT DEVELOPMENT


Kirk Hoff  
12/03/24



| TABLE OF CONTENTS  |   |                           |                    |  |                           | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|--------------------|---|---------------------------|--------------------|--|---------------------------|-------|----------------|-------------|-----------|
|                    |   |                           |                    |  |                           | ND    | HEN-3-999(059) | 2           | 1         |
| PLAN SECTIONS      |   |                           |                    |  | LIST OF STANDARD DRAWINGS |       |                |             |           |
| Section            | Page(s)                                   | Description               | Number             | Description  |                           |       |                |             |           |
| 1                  | 1   | Title Sheet               | D-101-1, 2,3,4     | NDDOT Abbreviations  |                           |       |                |             |           |
| 2                  | 1   | Table of Contents         | D-101-10           | NDDOT Utility Company and Organization Abbreviations                                     |                           |       |                |             |           |
| 4                  | 1 - 2                                     | Scope of Work             | D-101-20, 21       | Line Styles  |                           |       |                |             |           |
| 6                  | 1 - 3                                     | Notes                     | D-101-30, 31,32,33 | Symbols  |                           |       |                |             |           |
| 8                  | 1   | Quantities                | D-704-7            | Breakaway Systems For Construction Zone Signs - Perforated Tube                          |                           |       |                |             |           |
| 100                | 1   | Work Zone Traffic Control | D-704-8            | Breakaway Systems For Construction Zone Signs - U-Channel Post                           |                           |       |                |             |           |
| 110                | 1 - 12                                    | Signing                   | D-704-9            | Construction Sign Details - Terminal And Guide Signs                                     |                           |       |                |             |           |
| 120                | 1 - 4                                     | Pavement Marking          | D-704-10           | Construction Sign Details - Regulatory Signs   |                           |       |                |             |           |
| 140                | 1 - 4                                     | Lighting                  | D-704-11, 11A      | Construction Sign Details - Warning Signs  |                           |       |                |             |           |
| 150                | 1 - 10                                    | Signals                   | D-704-13           | Barricade And Channelizing Device Details  |                           |       |                |             |           |
| 160                | 1 - 3                                     | ITS                       | D-704-14           | Construction Sign Punching And Mounting Details  |                           |       |                |             |           |
|                    |   |                           | D-704-24           | Shoulder Closures And Bridge Painting Layouts  |                           |       |                |             |           |
|                    |   |                           | D-704-27           | Mobile Operation (Pavement Marking)  |                           |       |                |             |           |
|                    |   |                           | D-704-33           | Two-Lane Roadway Portable Rumble Strips  |                           |       |                |             |           |
|                    |   |                           | D-704-50           | Portable Sign Support Assembly   |                           |       |                |             |           |
|                    |   |                           | D-754-7            | Pipe Support And Sign Mounting Details   |                           |       |                |             |           |
|                    |   |                           | D-754-9            | Letter and Arrow Details   |                           |       |                |             |           |
|                    |   |                           | D-754-23           | Perforated Tube Assembly Details   |                           |       |                |             |           |
|                    |   |                           | D-754-24, 25       | Mounting Details Perforated Tube   |                           |       |                |             |           |
|                    |   |                           | D-754-24A          | Breakaway Coupler System For Perforated Tubes  |                           |       |                |             |           |
|                    |   |                           | D-754-27, 29,41    | Sign Punching, Stringer and Support Location Details Regulatory, Warning and Guide Signs |                           |       |                |             |           |
|                    |   |                           | D-754-49           | Sign Punching, Stringer and Support Location Details For Variable Length Signs           |                           |       |                |             |           |
|                    |   |                           | D-754-80           | Light Standard, Signal Standard, and Span Wire Mounted Sign Assembly Detail              |                           |       |                |             |           |
|                    |   |                           | D-762-1            | Pavement Marking Message Details   |                           |       |                |             |           |
|                    |   |                           | D-762-4            | Pavement Marking   |                           |       |                |             |           |
|                    |   |                           | D-770-1            | Concrete Foundations (Traffic Signals & Highway Lighting)                                |                           |       |                |             |           |
|                    |   |                           | D-772-2            | Traffic Signal Standards   |                           |       |                |             |           |
| SPECIAL PROVISIONS |   |                           |                    |  |                           |       |                |             |           |
| Number             | Description                               |                           |                    |  |                           |       |                |             |           |
| PSP 28(24)         | Permits and Environmental Considerations  |                           |                    |  |                           |       |                |             |           |
| SP 205(24)         | Tribal Employment Rights Ordinance (TERO) |                           |                    |  |                           |       |                |             |           |
| SP 245(24)         | Portable Changeable Message Signs         |                           |                    |  |                           |       |                |             |           |

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 4           | 1         |


Note  
6" & 12" wet reflective pavement marking through project limits



Scope of Work

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor





|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 4           | 2         |

Note  
6" & 12" wet reflective pavement marking through project limits

Scope of Work

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

REGISTERED PROFESSIONAL ENGINEER

Darell Arne

PE-6529

DATE  
12/03/24

NORTH DAKOTA



NOTES

GENERAL NOTES

100-P01

COORDINATION OF PROJECTS: Projects NH-3-020(142)097, PCN 24045 and NH-3-057(060)066, PCN 24044, are mill and overlay projects and expected to be constructed during the 2025 construction season. The projects are on ND 57 & ND 20 from Fort Totten to US 2.

Ensure pavement markings are installed after the project is complete. Coordinate this work with the Engineer.

107-100

LAWS TO BE OBSERVED: All or a portion of this project lies within the exterior boundaries of an Indian Reservation. Review laws and ordinances pertaining to the work contained within the boundaries of the reservation.

108-500

TERO COORDINATION: Invite the Tribal TERO Office to the Preconstruction Conference.

704-500

PORTABLE RUMBLE STRIPS (PRS): Use PRS made of rubber or engineered polymers.

Install PRS as part of the temporary traffic control when the following signs are also part of the required traffic control set up:

- “Be Prepared to Stop” (W3-4); and
- “Flagger” symbol (W20-7)

Install PRS that meet the following criteria:

- Have no adhesives or fasteners required for placement;
- Have a manufacture’s speed rating that meets or exceeds the posted speed limit; and
- Each strip in the array must weigh a minimum of 100 pounds.

Use individual PRS constructed in one of the following manners:

- A single piece;
- Interlocking segments; or
- Two pieces hinged at the midpoint.

An installed array of PRS consists of a minimum of 3 individual strips.

Move rumble strips with the flagging operations. Do not place rumble strips on horizontal curves.

The engineer will count and measure each array as one unit. Include the cost of providing, installing, maintaining, and relocating PRS in the unit price bid for “Portable Rumble Strips.”

704-P01

TRAFFIC CONTROL DEVICES LIST: The Traffic Control Devices List has been developed using the following Standard Drawing Layouts for traffic control:

- D-704-24 Type R: Two Lane Road Shoulder Closure
  - Sign installation
  - Road Closure Gate
- D-704-27 Mobile Operations: Two-Way Roadway
  - Pavement markings
- D-704-33 Two-Lane Roadway Portable Rumble Strips
  - In lane grooving/pavement marking messages
  - Embankment

The required traffic control signs and devices shown on the layout will be paid for at the unit price for the bid item “Traffic Control Signs.”

SECTION 110

754-P01

SOLAR VEHICLE SPEED FEEDBACK SIGN: Provide installation, programming, and maintenance manuals to the Engineer prior to installation. Submit work drawings with mounting details prior to installation. Ensure the Dynamic Speed Display sign and controller are compliant with the current edition of the MUTCD. Ensure the sign and equipment have a minimum 2-year warranty.

Provide a sign that follows the minimum standards shown below.

Static Sign Requirements:

- Center the message “YOUR SPEED” on the sign above the Dynamic Speed Display,
- Use series D or E font,
- Provide a black legend with yellow background, and
- Letter height 4”.

Feedback Sign Requirements:

- Sign dimensions 24”x30”,
- Digital number height 10”,
- Provide an LED display,
- Display the speed of the approaching vehicle as “XX” in MPH,
- Monitor traffic speed via radar detecting up to 1000 feet,
- Display legible at 1000 feet,
- Display face non-glare, UV resistant, and high impact polycarbonate,
- Weatherproof NEMA Type 3R rating,
- Display numerals yellow color,
- Operate at a temperature range of -34 degree C to +74 degree C,
- 22 degree viewing angle, and
- Type XI Retroreflective Sign Sheeting.

Controller Requirements:

- Programmable display for the posted speed limit,
- Blank or zero displayed when no advancing traffic is detected,
- Zero displayed when a vehicle exceeds the posted speed limit by 15 mph.
- Provide a controller that can take radar generated speed input and displaying it on the sign,
- Flash display at 50 to 60 cycles per minute if the detected speed exceeds the posted speed limit,
- Automatic nighttime dimming feature,
- Operates on solar power, and
- Operate 24 hours a day, 7 days a week.

Power Requirements:

- Provide solar panels to charge battery,
- Provide a solar charge controller,
- Provide AGM batteries sufficient to power the display sign for 3 days without sunlight, and

REGISTERED PROFESSIONAL ENGINEER

Darell Arrie

PE-6529

DATE 12/03/24

NORTH DAKOTA

11/27/2024 2:11:08 PM R:\project\30999000.059\Traffic\Sheets\006NT\_001\_notes.docm

| STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|-------|----------------|-------------|-----------|
| ND    | HEN-3-999(059) | 6           | 2         |

NOTES

- Install a ground wire and connect to a ground rod in the ground.

Sign Supports:

- Mount the dynamic speed display sign to the sign supports as shown in section 110.
- Securely fasten the ground wire to the sign supports using zip ties or other approved method.

Include costs associated with installation, supply, and testing of this sign equipment in the item “Vehicle Speed Feedback Sign”.

754-P02 BERM CONSTRUCTION: Install berm on ND 57 at RP 0.404 Rt and ND 20 at RP 101.345 Lt. Remove existing topsoil and store outside the clear zone. Place embankment according to section 203.04 G.4, Compaction Control, Type C. Place topsoil and apply Type II Seeding and mulch to all disturbed ground surfaces.

Include costs associated with this work in the item “Portable Changeable Message Sign.”

SECTION 120

762-050 PAVEMENT MARKING: If the Engineer and Contractor agree, plan quantity will be used as the measurement for payment for pavement marking items.

762-P01 EPOXY PVMT MK-WET REFLECTIVE: Supply epoxy pavement marking, and retroreflective optics as outlined below.

The following pavement marking products may be used:

- 3M Series 51E All Weather Elements, or
- Potters Visimax Beads, or
- Approved equal.

Use epoxy pavement marking paint as specified in the section 880.02 of the standard specifications.

Apply pavement markings as specified in Section 762.04 C.3, “Epoxy Paint Pavement Markings”, with the following exceptions:

- Apply retroreflective optics using a double drop system. The first drop shall consist of applying 3M Series 51E All Weather Elements at a rate of 4.2 pounds per gallon of paint. The second drop shall consist of applying the glass beads specified in Section 880.02 D at a rate of 20 pounds per gallon of paint. or
- Apply retroreflective optics using a double drop system. The first drop shall consist of applying Potters Visimax Beads at a rate of 6.0 pounds per gallon of paint. The second drop shall consist of applying the glass beads specified in Section 880.02 D at a rate of 6.0 pounds per gallon of paint.

Ensure a company representative is present during the initial application of the retroreflective optics.

Include all costs associated with this work in the price bid for the item “Epoxy Pvmt Mk 6in Line-Wet Reflective”, “Epoxy Pvmt Mk 6 in Line-Wet Reflective-Grooved”, and “Epoxy Pvmt Mk 12in Line-Wet Reflective-Grooved”.

SECTION 140

770-P01 FEED POINT: A new feed point will be installed on ND 20 at RP 101.26 Lt. Contact Nodak Electric Coop at the address below to set up the electrical service. Set up a new billing account with the NDDOT Devils Lake District.

Duddy Weisser  
Nodak Electric Coop  
4000 32<sup>nd</sup> Ave S  
Grand Forks, ND 58208  
(701) 795-6755  
[dweisser@nodakelectric.com](mailto:dweisser@nodakelectric.com)

Include all costs in the price bid for the item “Relocate Road Closure Gate”.

SECTION 150

772-P01 RRFB ASSEMBLY: Provide a Rectangular Rapid Flashing Beacon (RRFB) system that is operational as shown in the plans. This includes the following items:

- APS pedestrian push button actuation.
- RRFB LED unit.
- Mount the assembly on galvanized Type II posts or existing light standards.
- Provide galvanized transformer bases on all Type II posts.
- Cabinet with controller and locking cover.
- Program the flash rate and time according to the most current version of the MUTCD. Ensure the actuation is not less than 30 seconds.
- Mount RRFB LED unit and cabinet with vandal resistant hardware.
- Provide work drawings for this system as shown in Section 772.03.B “Work Drawings”.

Include costs associated with installation, supply, and testing of this sign equipment in the item “Flashing Beacon – Post Mounted”.

772-P02 ACCESSIBLE PEDESTRIAN SIGNALS (APS) PUSHBUTTON: Include the features, installation procedures, and be compliant with the following:

- A. Features:
- Rapid tick WALK indication, no more than 2–5dBA above ambient sound
  - Vibrotactile WALK indication
  - Speaker and vibrotactile indication located at pushbutton
  - Pushbutton locator tone
  - Tactile arrow on each device aligned in direction of travel on the crosswalk
- B. Installation Procedures
- APS should be reachable from the level landing of the curb ramp for the crossing or from a level surface with an accessible path to the ramp (MUTCD Section 4E.08 and Proposed and Draft PROWAG).
  - APS should be within 5 feet of the crosswalk line furthest from the center of the intersection and within 10 feet of the curb (MUTCD Section 4E.08).
  - Tactile arrow shall be aligned with parallel to the direction of travel on the crosswalk (MUTCD Section 4E.12, P1).



| STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|-------|----------------|-------------|-----------|
| ND    | HEN-3-999(059) | 6           | 2         |

NOTES

- Install a ground wire and connect to a ground rod in the ground.

Sign Supports:

- Mount the dynamic speed display sign to the sign supports as shown in section 110.
- Securely fasten the ground wire to the sign supports using zip ties or other approved method.

Include costs associated with installation, supply, and testing of this sign equipment in the item "Vehicle Speed Feedback Sign".

754-P02 BERM CONSTRUCTION: Install berm on ND 57 at RP 0.404 Rt and ND 20 at RP 101.345 Lt. Remove existing topsoil and store outside the clear zone. Place embankment according to section 203.04 E.4, Compaction Control, Type C. Place topsoil and apply Type II Seeding and mulch to all disturbed ground surfaces.

Include costs associated with this work in the item "Portable Changeable Message Sign."

SECTION 120

762-050 PAVEMENT MARKING: If the Engineer and Contractor agree, plan quantity will be used as the measurement for payment for pavement marking items.

762-P01 EPOXY PVMT MK-WET REFLECTIVE: Supply epoxy pavement marking, and retroreflective optics as outlined below.

The following pavement marking products may be used:

- 3M Series 51E All Weather Elements, or
- Potters Visimax Beads, or
- Approved equal.

Use epoxy pavement marking paint as specified in the section 880.02 of the standard specifications.

Apply pavement markings as specified in Section 762.04 C.3, "Epoxy Paint Pavement Markings", with the following exceptions:

- Apply retroreflective optics using a double drop system. The first drop shall consist of applying 3M Series 51E All Weather Elements at a rate of 5.3 pounds per gallon of paint. The second drop shall consist of applying the glass beads specified in Section 880.02 D at a rate of 20 pounds per gallon of paint. or
- Apply retroreflective optics using a double drop system. The first drop shall consist of applying Potters Visimax Beads at a rate of 6.0 pounds per gallon of paint. The second drop shall consist of applying the glass beads specified in Section 880.02 D at a rate of 6.0 pounds per gallon of paint.

Ensure a company representative is present during the initial application of the retroreflective optics.

Include all costs associated with this work in the price bid for the item "Epoxy Pvmt Mk 6in Line-Wet Reflective", "Epoxy Pvmt Mk 6 in Line-Wet Reflective-Grooved", and "Epoxy Pvmt Mk 12in Line-Wet Reflective-Grooved".

SECTION 140

770-P01 FEED POINT: A new feed point will be installed on ND 20 at RP 101.26 Lt. Contact Nodak Electric Coop at the address below to set up the electrical service. Set up a new billing account with the NDDOT Devils Lake District.

Duddy Weisser  
Nodak Electric Coop  
4000 32<sup>nd</sup> Ave S  
Grand Forks, ND 58208  
(701) 795-6755  
[dweisser@nodakelectric.com](mailto:dweisser@nodakelectric.com)

Include all costs in the price bid for the item "Relocate Road Closure Gate".

SECTION 150


772-P01 RRFB ASSEMBLY: Provide a Rectangular Rapid Flashing Beacon (RRFB) system that is operational as shown in the plans. This includes the following items:

- APS pedestrian push button actuation.
- RRFB LED unit.
- Mount the assembly on galvanized Type II posts or existing light standards.
- Provide galvanized transformer bases on all Type II posts.
- Cabinet with controller and locking cover.
- Program the flash rate and time according to the most current version of the MUTCD. Ensure the actuation is not less than 30 seconds.
- Mount RRFB LED unit and cabinet with vandal resistant hardware.
- Provide work drawings for this system as shown in Section 772.03.B "Work Drawings".

Include costs associated with installation, supply, and testing of this sign equipment in the item "Flashing Beacon – Post Mounted".

772-P02 ACCESSIBLE PEDESTRIAN SIGNALS (APS) PUSHBUTTON: Include the features, installation procedures, and be compliant with the following:

- A. Features:
1. Rapid tick WALK indication, no more than 2–5dBA above ambient sound
  2. Vibrotactile WALK indication
  3. Speaker and vibrotactile indication located at pushbutton
  4. Pushbutton locator tone
  5. Tactile arrow on each device aligned in direction of travel on the crosswalk
- B. Installation Procedures
1. APS should be reachable from the level landing of the curb ramp for the crossing or from a level surface with an accessible path to the ramp (MUTCD Section 4E.08 and Proposed and Draft PROWAG).
  2. APS should be within 5 feet of the crosswalk line furthest from the center of the intersection and within 10 feet of the curb (MUTCD Section 4E.08).
  3. Tactile arrow shall be aligned with parallel to the direction of travel on the crosswalk (MUTCD Section 4E.12, P1).



|       |                |             |           |
|-------|----------------|-------------|-----------|
| STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
| ND    | HEN-3-999(059) | 6           | 3         |

NOTES

4. Pushbutton required to be located within reach range for wheelchair users (Proposed PROWAG, R406).
- C. Code Compliance:
- 1. Functionality: MUTCD 2009 - 4E
  - 2. Temperature and Humidity: NEMA TS 2
  - 3. Transient Voltage Protection: NEMA TS 2
  - 4. Transient Suppression: IEC 61000-4-4, IEC 61000-4-5
  - 5. Electronic Noise: FCC Title 47, Part 15, Class A
  - 6. Mechanical Shock and Vibration: NEMA TS 2
  - 7. EN4 PBS Enclosure: NEMA 250 - Type 4X
  - 8. Electrical Reliability: NEMA TS 4

Include all costs associated with this item in the price bid for the item "Flashing Beacon – Post Mounted".



ESTIMATE OF QUANTITIES

|       |                |             |           |
|-------|----------------|-------------|-----------|
| STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
| ND    | HEN-3-999(059) | 8           | 1         |

| SPEC  | CODE  | ITEM DESCRIPTION                               | UNIT  | MAINLINE | TOTAL   |
|-------|-------|--|-------|----------|---------|
| ----- | ----- | -----  | ----- | -----    | -----   |
| 103   | 0100  | CONTRACT BOND                                  | L SUM | 0.18     | 0.18    |
| 702   | 0100  | MOBILIZATION                                   | L SUM | 0.18     | 0.18    |
| 704   | 0100  | FLAGGING                                       | MHR   | 100      | 100     |
| 704   | 1000  | TRAFFIC CONTROL SIGNS                          | UNIT  | 774      | 774     |
| 704   | 1048  | PORTABLE RUMBLE STRIPS                         | EA    | 2        | 2       |
| 704   | 1060  | DELINEATOR DRUMS                               | EA    | 35       | 35      |
| 704   | 1067  | TUBULAR MARKERS                                | EA    | 32       | 32      |
| 704   | 1087  | SEQUENCING ARROW PANEL-TYPE C                  | EA    | 1        | 1       |
| 754   | 0110  | FLAT SHEET FOR SIGNS-TYPE XI REFL SHEETING     | SF    | 407      | 407     |
| 754   | 0112  | FLAT SHEET FOR SIGNS-TYPE IV REFL SHEETING     | SF    | 39       | 39      |
| 754   | 0206  | STEEL GALV POSTS-TELESCOPING PERFORATED TUBE   | LF    | 629      | 629     |
| 754   | 0592  | RESET SIGN PANEL                               | EA    | 2        | 2       |
| 754   | 8005  | PORTABLE CHANGEABLE MESSAGE SIGN               | EA    | 2        | 2       |
| 754   | 8015  | VEHICLE SPEED FEEDBACK SIGN                    | EA    | 2        | 2       |
| 762   | 0122  | PREFORMED PATTERNED PVMT MK-MESSAGE(GROOVED)   | SF    | 1,429    | 1,429   |
| 762   | 0157  | EPOXY PVMT MK 6IN LINE-WET REFLECTIVE-GROOVED  | LF    | 257,791  | 257,791 |
| 762   | 0163  | EPOXY PVMT MK 12IN LINE-WET REFLECTIVE-GROOVED | LF    | 5,466    | 5,466   |
| 772   | 2110  | FLASHING BEACON-POST MOUNTED                   | EA    | 5        | 5       |
| 772   | 3150  | REMOVE FLASHING BEACON SYSTEM                  | EA    | 1        | 1       |
| 980   | 0800  | RELOCATE ROAD CLOSURE GATE                     | EA    | 1        | 1       |




[illegible][illegible]

|          |                       |             |     |
|----------|-----------------------|-------------|-----|
| 704-1000 | TRAFFIC CONTROL SIGNS | TOTAL UNITS | 774 |
|----------|-----------------------|-------------|-----|

[illegible]

VERSION: 11.21.2022



|   |  |
|---|--|
|  | <p>Sign Summary<br/>Perforated Tube</p> <p>ND 57/20 - US 281 to CR 1<br/>Vision Zero Safety Corridor</p> <p>ND Hwy 57 &amp; 20</p> |
|---|--|

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 3         |



ND Hwy 57

Sign 1

Safety Corridor  
VISION ZERO  
Zero Fatalities. Zero Excuses.

RP 0.314 Rt

Signing Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 4         |


| SPEC  | CODE | BID ITEM  | QTY           | UNIT     |
|-------|------|---|---------------|----------|
| 754   | 8015 | VEHICLE SPEED FEEDBACK SIGN<br>RP 4,303 Rt  | 1             | EA       |
| 762   | 0122 | Preformed Patterned Pvmnt Mkg-Message(grooved)<br>REDUCED SPEED AHEAD (x1)<br>40 MPH (x1) | 103.1<br>30.6 | SF<br>SF |
| Total |      |   | 133.7         | SF       |

Signing and Pavement Marking Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor


ND Hwy 57







|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 6         |



Signing Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57



REGISTERED PROFESSIONAL ENGINEER

**Darell Arne**

PE-6529

DATE  
12/03/24

NORTH DAKOTA



ND Hwy 57



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 8         |

| SPEC  | CODE | BID ITEM  | QTY           | UNIT     |
|-------|------|---|---------------|----------|
| 754   | 8015 | VEHICLE SPEED FEEDBACK SIGN<br>RP 101.506 Rt  | 1             | EA       |
| 762   | 0122 | Preformed Patterned Pvmnt Mkg-Message(grooved)<br>REDUCED SPEED AHEAD (x1)<br>45 MPH (x1) | 103.1<br>30.8 | SF<br>SF |
| Total |      |   | 133.9         | SF       |


  

Signing and Pavement Marking Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 20

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 9         |



Sign and Pavement Marking Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57 & ND Hwy 20






|   |                   |
|---|-------------------|
| STATION(S):<br>ND 20 - RP 101,619 Lt<br>ND 57 - RP 0,314 Rt | AREA: 19.5 Sq.Ft. |
|---|-------------------|

Technical drawing of a 'Safety Corridor' sign. The sign is rectangular with a black background and white text. The text reads 'Safety Corridor' in a large, bold, sans-serif font, followed by 'VISION ZERO' in a smaller, bold, sans-serif font, and 'Zero Fatalities. Zero Excuses.' in a smaller, regular, sans-serif font. The sign is mounted on a post. Dimensions are provided in inches and feet. The overall width is 6'-6" (63.9" + 7.05" + 7.05"). The overall height is 3'-0" (25.3" + 25.3" + 4" + 4" + 6.75" + 6.75"). The sign itself is 63.9" wide and 25.25" high. The mounting post is 7.05" wide and 25.25" high. The sign is 4" from the top and bottom of the post. The sign is 6.75" from the left and right sides of the post. The sign is 6.75" from the top and bottom of the post.

Dimensions are in inches.tenths

Letter locations are panel edge to lower left corner

PANEL STYLE: ND\_Conv\_Boundary.ssi

[illegible]

**Note: An image of the Vision Zero logo can be obtained from the Design Division.**


ND Hwy 57 &amp; ND Hwy 20




|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 11        |

(A) Refer to manufacturer recommendations for mounting to sign supports.


(B) Refer to manufacturer recommendations for solar panel mounting and orientation.




Special Assembly A  
Solar Powered Vehicle Speed Feedback Sign  
ND 57 - RP 4.303 Rt  
ND 20 - RP 101.506 Rt



Special Assembly B  
Back-to-Back (see detail)  
Rectangular Rapid Flashing Beacon  
ND 57 - RP 4.573 Rt  
RP 4.682 Lt  
RP 6.145 Rt  
RP 6.145 Lt



Special Assembly C  
Back-to-Back (see detail)  
Rectangular Rapid Flashing Beacon  
ND 57 - RP 5.012 Rt  
RP 6.019 Rt



Back-to-Back Detail  
Rectangular Rapid Flashing Beacon


Sign Assemblies

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor


ND Hwy 57 & ND Hwy 20




|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 110         | 12        |



Special Assembly D  
ND 57  
RP 4.515 Rt  
RP 4.740 Lt  
RP 6.087 Rt  
RP 6.183 Lt



Special Assembly E  
ND 57  
RP 4.954 Rt  
RP 5.070 Lt  
RP 5.961 Rt  
RP 6.078 Lt



Special Assembly F  
ND 57  
RP 4.365 Rt  
RP 4.836 Lt

Sign Assemblies

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 120         | 1         |

| Location                    | Preformed Patterned Pvmt Mk-Message (Grooved) |                 | 6" wet refl epoxy grooved   |                              |                               |                     |                     | 12" wet refl epoxy grooved |
|-----------------------------|---|-----------------|-----------------------------|------------------------------|-------------------------------|---------------------|---------------------|----------------------------|
|                             | Right Turn Arrow                              | Left Turn Arrow | 6" yellow left barrier line | 6" yellow right barrier line | 6" yellow double barrier line | 6" yellow edge line | 6" white centerline | 12" white channel line     |
| ND 20 - CR 1 to Jct ND 57   | 3   | 9               | 2650                        | 1740                         | 10584                         | 41670               | 3475                | 1484                       |
| ND 57 - US 281 to Jct ND 20 | 22  | 19              | 4028                        | 3081                         | 27194                         | 140205              | 13714               | 3982                       |
| Totals                      | 25  | 28              | 6678                        | 4821                         | 37778                         | 181875              | 17189               | 5466                       |

| SPEC | CODE | BID ITEM                                       | QTY    | UNIT |
|------|------|--|--------|------|
| 762  | 0122 | PREFORMED PATTERNED PVMT MK-MESSAGE(GROOVED)   |        |      |
|      |      | Right Turn Arrow (x25)                         | 400    | SF   |
|      |      | Left Turn Arrow (x28)                          | 448    | SF   |
|      |      | DO NOT PASS (x6)                               | 312    | SF   |
|      |      | Total  | 1160   | SF   |
| 762  | 0157 | EPOXY PVMT MK 6IN LINE-WET REFLECTIVE-GROOVED  |        |      |
|      |      | 6" white edge line                             | 181875 | LF   |
|      |      | 6" yellow lane line                            | 17189  | LF   |
|      |      | 6" yellow left barrier line                    | 9489   | LF   |
|      |      | 6" yellow right barrier line                   | 7204   | LF   |
|      |      | 6" yellow double barrier line                  | 42034  | LF   |
|      |      | Total  | 257791 | LF   |
| 762  | 0163 | EPOXY PVMT MK 12IN LINE-WET REFLECTIVE-GROOVED |        |      |
|      |      | 12" white channel line                         | 5466   | LF   |

| Hwy                      | Location of No Passing Zone along |           | 6" wet refl epoxy grooved    |                             |                               |
|--------------------------|-----------------------------------|-----------|------------------------------|-----------------------------|-------------------------------|
|                          |                                   |           | 6" yellow right barrier line | 6" yellow left barrier line | 6" double yellow barrier line |
| ND 20                    | start and stop location           | direction | NB/EB passing restricted     | SB\WB passing restricted    |                               |
|                          |                                   |           |                              |                             |                               |
|                          | RP 101.205 to RP 100.818          | SB        |                              | 1656                        | 1436                          |
| RP 100.660 to RP 100.954 | NB                                | 1043      |                              |                             |                               |
| ND 57                    |                                   |           |                              |                             |                               |
|                          | RP 3.61 to RP 3.168               | WB        |                              | 1155                        | 2820                          |
|                          | RP 2.965 to RP 3.435              | EB        | 1340                         |                             |                               |
|                          | Totals                            |           | 2383                         | 2811                        | 4256                          |

| Location   |    | pvmt mkg message |
|------------|----|------------------|
|            |    | DO NOT PASS      |
| RP 101.205 | SB | 1                |
| RP 100.660 | NB | 1                |
| RP 4.675   | WB | 1                |
| RP 4.16    | EB | 1                |
| RP 3.61    | WB | 1                |
| RP 2.965   | EB | 1                |
| Total      |    | 6                |



Pavement Marking

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57 & ND Hwy 20



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 120         | 2         |



Pavement Marking Details




ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57 & ND Hwy 20







|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 120         | 3         |





5.3 S. F.




6.3 S. F.



6.1 S. F.



19.2 S. F.




Pavement Marking Details

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor


ND Hwy 57 & ND Hwy 20




|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 120         | 4         |




22.4 SF




5.6 SF




5.4 SF




6.1 SF




5.7 SF




29.6 SF



6.4 SF



7.1 SF




3.9 SF

Pavement Marking Details

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57 & ND Hwy 20





|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 140         | 1         |

Road Closure Gate Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 20


REGISTERED PROFESSIONAL ENGINEER

**Darell Arne**

PE-6529

DATE 12/03/24

NORTH DAKOTA



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 140         | 3         |

| Road Closure Gate Quantities (A)                           |    |     |
|--|----|-----|
| Underground Conductor No 4 Type RHW                        | LF | 246 |
| Underground Conductor No 6 Type RHW                        | LF | 146 |
| Underground Conductor No 6 Type THW                        | LF | 196 |
| No 14 AWG 5 Conductor Cable                                | LF | 69  |
| 2 Inch Diameter Conduit                                    | LF | 196 |
| Reset Light Standard with Road Closure Gate System         | EA | 1   |
| Concrete Foundation - Highway Lighting                     | EA | 1   |
| Reset Pedestal Mounted Cabinet on new concrete foundation  | EA | 1   |
| Reset Switch Box Pipe Stand Mounted                        | EA | 1   |
| Feed Point Pipe Stand Mounted                              | EA | 1   |
| Seeding & Mulch  | SY | 40  |
| Remove Road Closure Gate Foundation and Cabinet Foundation | EA | 1   |

| SPEC | CODE | BID ITEM                   | QTY | UNIT |
|------|------|----------------------------|-----|------|
| 980  | 0800 | Relocate Road Closure Gate |     |      |
|      |      |                            | 1   | EA   |

(A) Include these quantities in the price bid for the item "Relocate Road Closure Gate"

| Road Closure Gate - Cable & Conduit Chart |              |        |            |                              |
|---|--------------|--------|------------|------------------------------|
| Location                                  | Conduit Runs |        | Cable Runs |                              |
|   | LF           | DIA IN | LF         | Type                         |
| Light Std with Gate to                    |              |        | 69         | No 14 AWG 5                  |
| Cabinet                                   | 43           | 2      | 86<br>43   | (2) No 6 RHW<br>(1) No 6 THW |
| Cabinet to<br>Switch Box                  | 30           | 2      | 60<br>30   | (2) No 6 RHW<br>(1) No 6 THW |
| Switch Box to<br>bore location            | 123          | 2      | 246<br>123 | (2) No 4 RHW<br>(1) No 6 THW |

Road Closure Gate Quantities

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 20

REGISTERED PROFESSIONAL ENGINEER

Darell Arne

PE-6529


DATE 12/03/24

NORTH DAKOTA

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 140         | 4         |

NOTES:  
When mounting the Road closure gate on the light standard, the luminaire arm will be rotated slightly to allow the gate to be stowed in the upright position.

\*See Standard D-770-1 for additional Light & Signal Standard Foundation details




| TABLE 1              |            |
|----------------------|------------|
| Concrete Foundation* |            |
| Depth                | Diameter   |
| 6'                   | 24" or 30" |
| 5'                   | 36" or 42" |


Reset Existing Light Standard  
with Road Closure Gate


ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 20









|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 2         |

Flashing Beacon Removal Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57

REGISTERED PROFESSIONAL ENGINEER

**Darell Arne**

PE-6529

DATE 12/03/24

NORTH DAKOTA

| Removal Quantities (A)  |    |   |
|---|----|---|
| Remove flashing beacon head, and push button from light standard                      | EA | 4 |
| Remove flashing beacon head, steel conduit, push button, and perforated tube supports | EA | 6 |
| Remove flasher cabinet and supports   | EA | 1 |
|   |    |   |

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 3         |

| SPEC | CODE | BID ITEM                      | QTY | UNIT |
|------|------|-------------------------------|-----|------|
| 772  | 3150 | Remove Flashing Beacon System |     |      |
|      |      |                               | 1   | EA   |

(A) Include these quantities in the price bid for the item "Remove Flashing Beacon System."

Flashing Beacon Removal Quantities

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57





| RRFB 1 Quantities (A)   |    |     |
|---|----|-----|
| Pull Box  | EA | 1   |
| Underground Conductor No 6 Type RHW                               | LF | 118 |
| Underground Conductor No 6 Type THW                               | LF | 59  |
| No 14 AWG 7 Conductor Cable                                       | LF | 178 |
| 2 Inch Diameter Conduit   | LF | 66  |
| Rectangular Rapid Flashing Beacon assembly-light standard mounted | EA | 2   |
| Rectangular Rapid Flashing Beacon assembly-post mounted           | EA | 2   |
| APS Pushbutton Assembly   | EA | 2   |
| Post Type II with concrete foundation                             | EA | 1   |
| RRFB cabinet post mounted   | EA | 1   |
| Seeding & Mulch   | SY | 10  |
| Revise lighting and flashing beacon feed point                    | EA | 1   |

| RRFB 2 Quantities (A)   |    |      |
|---|----|------|
| Pull Box  | EA | 1    |
| Underground Conductor No 6 Type RHW                               | LF | 1284 |
| Underground Conductor No 6 Type THW                               | LF | 642  |
| No 14 AWG 7 Conductor Cable                                       | LF | 160  |
| 2 Inch Diameter Conduit   | LF | 698  |
| Rectangular Rapid Flashing Beacon assembly-light standard mounted | EA | 2    |
| Rectangular Rapid Flashing Beacon assembly-post mounted           | EA | 2    |
| APS Pushbutton Assembly   | EA | 2    |
| Post Type II with concrete foundation                             | EA | 1    |
| RRFB cabinet post mounted   | EA | 1    |
| Seeding & Mulch   | SY | 150  |
| Revise flasher cabinet  | EA | 1    |

| RRFB 1 Cable & Conduit Chart                       |              |        |            |                              |
|--|--------------|--------|------------|------------------------------|
| Location   | Conduit Runs |        | Cable Runs |                              |
|  | LF           | DIA IN | LF         | Type                         |
| RRFB 1a Pole Mtd to<br>RRFB 1b Lt Std Mtd          | 66           | 2      | 130        | No 14 AWG 7                  |
| RRFB 1b Lt Std Mtd to<br>RRFB 1b Jct Box           |              |        | 48         | No 14 AWG 7                  |
| RRFB 1b Jct Box to<br>Existing Itg & FB Feed Point | 57           | 2      | 118<br>59  | (2) No 6 RHW<br>(1) No 6 THW |

| RRFB 2 Cable & Conduit Chart                  |              |        |             |                              |
|---|--------------|--------|-------------|------------------------------|
| Location                                      | Conduit Runs |        | Cable Runs  |                              |
|   | LF           | DIA IN | LF          | Type                         |
| RRFB 2a Pole Mtd to<br>RRFB 2b Lt Std Mtd     | 64           | 2      | 112         | No 14 AWG 7                  |
| RRFB 2b Lt Std Mtd to<br>RRFB 2b Jct Box      |              |        | 48          | No 14 AWG 7                  |
| RRFB 2b Jct Box to<br>Pull box 1              | 581          | 2      | 1172<br>586 | (2) No 6 RHW<br>(1) No 6 THW |
| Pull box 1 to<br>Existing Itg & FB Feed Point | 53           | 2      | 112<br>56   | (2) No 6 RHW<br>(1) No 6 THW |

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 5         |

| SPEC | CODE | BID ITEM                       | QTY | UNIT |
|------|------|--------------------------------|-----|------|
| 772  | 2110 | Flashing Beacon - Post Mounted |     |      |
|      |      |                                | 2   | EA   |

(A) Include these quantities in the price bid for the item "Flashing Beacon - Post Mounted".



RRFB Quantities

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 6         |



RRFB Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57





|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 7         |

| SPEC | CODE | BID ITEM                       | QTY | UNIT |
|------|------|--------------------------------|-----|------|
| 772  | 2110 | Flashing Beacon - Post Mounted |     |      |
|      |      |                                | 1   | EA   |

(A) Include these quantities in the price bid for the item "Flashing Beacon - Post Mounted".

| RRFB 3 Quantities (A)   |    |     |
|---|----|-----|
| Pull Box  | EA | 1   |
| Underground Conductor No 6 Type RHW                               | LF | 482 |
| Underground Conductor No 6 Type THW                               | LF | 241 |
| No 14 AWG 7 Conductor Cable                                       | LF | 160 |
| 2 Inch Diameter Conduit   | LF | 301 |
| Rectangular Rapid Flashing Beacon assembly-light standard mounted | EA | 2   |
| Rectangular Rapid Flashing Beacon assembly-post mounted           | EA | 2   |
| APS Pushbutton Assembly   | EA | 2   |
| Post Type II with concrete foundation                             | EA | 1   |
| RRFB cabinet post mounted   | EA | 1   |
| Seeding & Mulch   | SY | 55  |
| Revise lighting and flashing beacon feed point                    | EA | 1   |

| RRFB 3 Cable & Conduit Chart                  |              |        |            |                              |
|---|--------------|--------|------------|------------------------------|
| Location                                      | Conduit Runs |        | Cable Runs |                              |
|   | LF           | DIA IN | LF         | Type                         |
| RRFB 3a Lt Std Mtd to<br>RRFB 3b Pole Mtd     | 68           | 2      | 112        | No 14 AWG 7                  |
| RRFB 3b Pole Mtd to<br>RRFB 3b Jct Box        |              |        | 48         | No 14 AWG 7                  |
| RRFB 3b Jct Box to<br>Pull box 2              | 161          | 2      | 162<br>166 | (2) No 6 RHW<br>(1) No 6 THW |
| Pull box 2 to<br>Existing Itg & FB Feed Point | 72           | 2      | 150<br>75  | (2) No 6 RHW<br>(1) No 6 THW |

RRFB Quantities

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57


REGISTERED PROFESSIONAL ENGINEER

Darell Arne

PE-6529

DATE 12/03/24

NORTH DAKOTA



|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 8         |

RRFB Layout

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57

REGISTERED PROFESSIONAL ENGINEER

**Darell Arne**

PE-6529

DATE  
12/03/24

NORTH DAKOTA

|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 9         |

| SPEC | CODE | BID ITEM                       | QTY | UNIT |
|------|------|--------------------------------|-----|------|
| 772  | 2110 | Flashing Beacon - Post Mounted |     |      |
|      |      |                                | 2   | EA   |

(A) Include these quantities in the price bid for the item "Flashing Beacon - Post Mounted".

| RRFB 4 Quantities (A)   |    |     |
|---|----|-----|
| Pull Box  | EA | 1   |
| Underground Conductor No 6 Type RHW                               | LF | 428 |
| Underground Conductor No 6 Type THW                               | LF | 214 |
| No 14 AWG 7 Conductor Cable                                       | LF | 162 |
| 2 Inch Diameter Conduit   | LF | 274 |
| Rectangular Rapid Flashing Beacon assembly-light standard mounted | EA | 2   |
| Rectangular Rapid Flashing Beacon assembly-post mounted           | EA | 2   |
| APS Pushbutton Assembly   | EA | 2   |
| Post Type II with concrete foundation                             | EA | 1   |
| RRFB cabinet post mounted   | EA | 1   |
| Seeding & Mulch   | SY | 50  |
| Revise lighting and flashing beacon feed point                    | EA | 1   |

| RRFB 4 Cable & Conduit Chart |              |        |            |                              |
|------------------------------|--------------|--------|------------|------------------------------|
| Location                     | Conduit Runs |        | Cable Runs |                              |
|                              | LF           | DIA IN | LF         | Type                         |
| RRFB 4a Pole Mtd to          | 68           | 2      | 114        | No 14 AWG 7                  |
| RRFB 4b Lt Std Mtd           |              |        |            |                              |
| RRFB 4b Lt Std Mtd to        |              |        | 48         | No 14 AWG 7                  |
| RRFB 4b Jct Box              |              |        |            |                              |
| RRFB 4b Jct Box to           | 148          | 2      | 306<br>153 | (2) No 6 RHW<br>(1) No 6 THW |
| Pull box 3                   |              |        |            |                              |
| Pull box 3 to                | 58           | 2      | 122<br>61  | (2) No 6 RHW<br>(1) No 6 THW |
| Existing Itg & FB Feed Point |              |        |            |                              |

| RRFB 5 Quantities (A)                                   |    |      |
|---|----|------|
| Underground Conductor No 6 Type RHW                     | LF | 1176 |
| Underground Conductor No 6 Type THW                     | LF | 588  |
| No 14 AWG 7 Conductor Cable                             | LF | 180  |
| 2 Inch Diameter Conduit                                 | LF | 666  |
| Rectangular Rapid Flashing Beacon assembly-post mounted | EA | 2    |
| APS Pushbutton Assembly                                 | EA | 2    |
| Post Type II with concrete foundation                   | EA | 1    |
| RRFB cabinet post mounted                               | EA | 1    |
| Seeding & Mulch   | SY | 120  |

| RRFB 5 Cable & Conduit Chart |              |        |             |                              |
|------------------------------|--------------|--------|-------------|------------------------------|
| Location                     | Conduit Runs |        | Cable Runs  |                              |
|                              | LF           | DIA IN | LF          | Type                         |
| RRFB 5a Pole Mtd to          | 88           | 2      | 132         | No 14 AWG 7                  |
| RRFB 5b Pole Mtd             |              |        |             |                              |
| RRFB 5b Pole Mtd to          |              |        | 48          | No 14 AWG 7                  |
| RRFB 5b Jct Box              |              |        |             |                              |
| RRFB 5b Jct Box to           | 520          | 2      | 1054<br>527 | (2) No 6 RHW<br>(1) No 6 THW |
| Pull box 3                   |              |        |             |                              |
| Pull box 3 to                | 58           | 2      | 122<br>61   | (2) No 6 RHW<br>(1) No 6 THW |
| Existing Itg & FB Feed Point |              |        |             |                              |

RRFB Quantities


ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57




|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 150         | 10        |

- (A) See standard drawing D-772-2 for details on the Type II post and installation details. See standard drawing D-754-80 for light standard mounting details.
- (B) Install the cabinet on the post opposite from the push button on the flashing beacon assembly that is closest to the feed point.
- (C) The pushbutton and sign are to face the crosswalk.
- (D) See standard drawing D-770-1 for post foundation details. Refer to the foundation size table below.



Front View  
Post Mounted RRFB Assembly



Side View


| Traffic Signal Foundation Table |                                      |                                      |
|---------------------------------|--------------------------------------|--------------------------------------|
| Type II Signal Standard         |                                      |                                      |
| Description                     | Footing Depth "D"<br>24" and 30" Dia | Footing Depth "D"<br>36" and 42" Dia |
| Signal Standard                 | 4'                                   | 3'                                   |

RRFB Details

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57





|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 160         | 1         |

| SPEC | CODE | BID ITEM  | QTY | UNIT |
|------|------|---|-----|------|
| 754  | 8005 | PORTABLE CHANGEABLE MESSAGE SIGN<br>RP 101.345 Lt | 1   | EA   |

| Quantities (A)                                 |    |    |
|--|----|----|
| Borrow/Excavation Type C                       | CY | 50 |
| 4" Concrete Slab                               | EA | 1  |
| Remove/Replace Topsoil                         | CY | 12 |
| Portable Changeable Message Sign Solar Powered | EA | 1  |
| Seeding & Mulch                                | SY | 93 |

- (A) Include these quantities in the price bid for item "Portable Changeable Message Sign."  
(B) Install the CMS sign on the berm as shown.


Berm Details  
Changeable Message Sign

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 20



| SPEC | CODE | BID ITEM  | QTY | UNIT |
|------|------|---|-----|------|
| 754  | 8005 | PORTABLE CHANGEABLE MESSAGE SIGN<br>RP 0.404 Rt | 1   | EA   |



(A) Include these quantities in the price bid for item "Portable Changeable Message Sign."  
(B) Install the CMS sign on the berm as shown.

## Berm Details

### Changeable Message Sign


ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57





|  |       |                |             |           |
|--|-------|----------------|-------------|-----------|
|  | STATE | PROJECT NO.    | SECTION NO. | SHEET NO. |
|  | ND    | HEN-3-999(059) | 160         | 3         |



Berm Typical Sections  
Changeable Message Sign

ND 57/20 - US 281 to CR 1  
Vision Zero Safety Corridor

ND Hwy 57 & ND Hwy 20



NDDOT ABBREVIATIONS

D-101-1

|        |   |                     |  |                      |                              |        |                           |
|--------|---|---------------------|--|----------------------|------------------------------|--------|---------------------------|
| ?      | This is a special text character used in the labeling of existing features. It indicates a feature that has an unknown characteristic, potentially based on: lack of description, location accuracy or purpose. | C Gdrl              | cable guardrail                          | Culv                 | culvert                      | FOS    | factor of safety          |
| Abn    | abandoned   | Calc                | calculate                                | C&G                  | curb & gutter                | Fed    | Federal                   |
| Abut   | abutment  | CIP                 | cast iron pipe                           | CI                   | curb inlet                   | FP     | feed point                |
| Adj    | adjusted  | CB                  | catch basin                              | CR                   | curb ramp                    | Fn     | fence                     |
| Aggr   | aggregate   | CRS                 | cationic rapid setting                   | C                    | cut                          | Fn P   | fence post                |
| Ahd    | ahead   | C Gd                | cattle guard                             | Dd Ld                | dead load                    | FO     | fiber optic               |
| ARV    | air release valve   | C To C              | center to center                         | Defl                 | deflection                   | FD     | field drive               |
| Align  | alignment   | CL or $\varnothing$ | centerline                               | Defm                 | deformed                     | F      | fill                      |
| Al     | alley   | Ch                  | chain                                    | DInt                 | delineate                    | FAA    | fine aggregate angularity |
| Alt    | alternate   | Chnlk               | chain-link                               | DIntr                | delineator                   | FH     | fire hydrant              |
| Alum   | aluminum  | Ch Blk              | channel block                            | Depr                 | depression                   | FI     | flange                    |
| ADA    | Americans with Disabilities Act   | Ch Ch               | channel change                           | Desc                 | description                  | FIRD   | flared                    |
| &      | and   | Chk                 | check                                    | Det                  | detail                       | FES    | flared end section        |
| Appr   | approach  | Chsld               | chiseled                                 | DWP                  | detectable warning panel     | F Bcn  | flashing beacon           |
| Approx | approximate   | Cir                 | circle                                   | Dtr                  | detour                       | FA     | flight auger sample       |
| ACP    | asbestos cement pipe  | Cl                  | class                                    | Dia or $\varnothing$ | diameter                     | FL     | flow line                 |
| Asph   | asphalt   | Clnt                | clean-out                                | Dir                  | direction                    | Ftg    | footing                   |
| AC     | asphalt cement  | Clr                 | clear                                    | Dist                 | distance                     | FM     | force main                |
| Assmd  | assumed   | Cl&gr               | clearing & grubbing                      | DM                   | disturbed material           | Fnd    | found                     |
| @      | at  | Comb.               | combination                              | DB                   | ditch block                  | Fdn    | foundation                |
| Atten  | attenuation   | Coml                | commercial                               | DG                   | ditch grade                  | Frac   | fractional                |
| ATR    | automatic traffic recorder  | Compr               | compression                              | Dbl                  | double                       | Frwy   | freeway                   |
| Ave    | Avenue  | CADD                | computer aided drafting & design         | Dn                   | down                         | Frt    | front                     |
| Avg    | average   | Conc                | concrete                                 | Dwg                  | drawing                      | FF     | front face                |
| ADT    | average daily traffic   | CECB                | concrete erosion control blanket         | Dr                   | drive                        | F Disp | fuel dispenser            |
|        |   | Cond                | conductor                                | Drw                  | driveway                     | FFP    | fuel filler pipes         |
|        |   | Const               | construction                             | DI                   | drop inlet                   | FLS    | fuel leak sensor          |
|        |   | Cont                | continuous                               | D                    | dry density                  | Furn   | furnish/ed                |
|        |   | CSB                 | continuous split barrel sample           |                      |                              |        |                           |
|        |   | Contr               | contraction                              |                      |                              |        |                           |
|        |   | Contr               | contractor                               |                      |                              |        |                           |
|        |   | CP                  | control point                            |                      |                              |        |                           |
| Bk     | back  | Coord               | coordinate                               | Ea                   | each                         |        |                           |
| BF     | back face   | Cor                 | corner                                   | Esmt                 | easement                     |        |                           |
| Balc   | balcony   | Corr                | corrected                                | E                    | East                         |        |                           |
| B Wire | barbed wire   | CAES                | corrugated aluminum end section          | EB                   | Eastbound                    |        |                           |
| Barr   | barricade   | CAP                 | corrugated aluminum pipe                 | Elast                | elastomeric                  |        |                           |
| Btry   | battery   | CMES                | corrugated metal end section             | EL                   | electric locker              |        |                           |
| BI     | beehive inlet   | CMP                 | corrugated metal pipe                    | E Mtr                | electric meter               |        |                           |
| Beg    | begin   | CPVCP               | corrugated poly-vinyl chloride pipe      | Elec                 | electric/al                  |        |                           |
| BG     | below grade   | CSES                | corrugated steel end section             | EDM                  | electronic distance meter    |        |                           |
| BM     | bench mark  | CSFES               | corrugated steel flared end section      | Elev or El           | elevation                    |        |                           |
| Bkwy   | bikeway   | CSP                 | corrugated steel pipe                    | Ellipt               | elliptical                   |        |                           |
| Bit    | bituminous  | CSTES               | corrugated steel traversable end section | Emb                  | embankment                   |        |                           |
| Blk    | block   | Co                  | County                                   | Emuls                | emulsion/emulsified          |        |                           |
| BH     | bore hole   | Crse                | course                                   | ES                   | end section                  |        |                           |
| Bot    | bottom  | Ct                  | Court                                    | Engr                 | engineer                     |        |                           |
| Blvd   | Boulevard   | Xarm                | cross arm                                | ESS                  | environmental sensor station |        |                           |
| Bndry  | boundary  | Xbuck               | cross buck                               | Eq                   | equal                        |        |                           |
| Brkwy  | breakaway   | Xsec                | cross sections                           | Evgr                 | evergreen                    |        |                           |
| Br     | bridge  | Xing                | crossing                                 | Exc                  | excavation                   |        |                           |
| Bldg   | building  | Xrd                 | crossroad                                | Exst                 | existing                     |        |                           |
| Bus.   | business  | Crn                 | crown                                    | Exp                  | expansion                    |        |                           |
| BV     | butterfly valve   |                     |  | Expy                 | Expressway                   |        |                           |
| Byp    | bypass  |                     |  | E                    | external of curve            |        |                           |
|        |   |                     |  | Extru                | extruded                     |        |                           |

|  |  |
|--|--|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |  |
| 07-01-14                                     |  |
| REVISIONS                                    |  |
| DATE   | CHANGE   |
| 04-23-18<br>09-20-18<br>12-10-20<br>08-16-22 | General Revisions<br>General Revisions<br>General Revisions<br>General Revisions |


08/16/22

## NDDOT ABBREVIATIONS

D-101-2

|        |                              |          |                          |                      |                               |          |   |
|--------|------------------------------|----------|--------------------------|----------------------|-------------------------------|----------|---|
| Galv   | galvanized                   | Ln       | lane                     | Obsc                 | obscure(d)                    | Qty      | quantity                                    |
| Gar    | garage                       | Lg       | large                    | Ocpd                 | occupied                      | Qtr      | quarter                                     |
| Gs L   | gas line                     | Lat      | latitude                 | Ocpy                 | occupy                        |          |   |
| G Reg  | gas line regulator           | Lt       | left                     | O/s                  | offset                        |          |   |
| GMV    | gas main valve               | Lens     | lenses                   | OC                   | on center                     | Rad or R | radius                                      |
| G Mtr  | gas meter                    | Lvl      | level                    | C                    | one dimensional consolidation | RR       | railroad                                    |
| GSV    | gas service valve            | LvIng    | leveling                 | OC                   | organic content               | Rlwy     | railway                                     |
| GVP    | gas vent pipe                | Lht      | light                    | Orig                 | original                      | Rsd      | raised                                      |
| GV     | gate valve                   | LP       | light pole               | O To O               | out to out                    | RC       | rapid curing                                |
| Ga     | gauge                        | Ltg      | lighting                 | OD                   | outside diameter              | Rec      | record                                      |
| Gov    | government                   | Liq      | liquid                   | OH                   | overhead                      | Rcy      | recycle                                     |
| Grd    | graded/grade                 | LL       | liquid limit             |                      |                               | RAP      | recycled asphalt pavement                   |
| Grnd   | ground                       | Loc      | location                 |                      |                               | RPCC     | recycled portland cement concrete           |
| GWM    | ground water monitor         | Long.    | longitude                | PMT                  | pad mounted transformer       | Ref      | reference                                   |
| Gdrl   | guardrail                    | Lp       | loop                     | Pg                   | pages                         | R Mkr    | reference marker                            |
| Gtr    | gutter                       | LD       | loop detector            | Pntd                 | painted                       | RM       | reference monument                          |
|        |                              | Lum      | luminaire                | Pr                   | pair                          | RP       | reference point                             |
|        |                              |          |                          | Pnl                  | panel                         | Refl     | reflectorized                               |
| H Plg  | H piling                     |          |                          | Pk                   | park                          | RCB      | reinforced concrete box                     |
| Hdwl   | headwall                     | Mb       | mailbox                  | PSD                  | passing sight distance        | RCES     | reinforced concrete end section             |
| Ht     | height                       | ML       | main line                | Pvmt                 | pavement                      | RCFES    | reinforced concrete flared end section      |
| Hel    | helical                      | MH       | manhole                  | Ped                  | pedestal                      | RCP      | reinforced concrete pipe                    |
| HDPE   | high density polyethylene    | Mkd      | marked                   | Ped                  | pedestrian                    | RCPS     | reinforced concrete pipe sewer              |
| HM     | high mast                    | Mkr      | marker                   | PPP                  | pedestrian pushbutton post    | RCTES    | reinforced concrete traversable end section |
| HP     | high pressure                | Mkg      | marking                  | Pen.                 | penetration                   | Reinf    | reinforcement                               |
| HPS    | high pressure sodium         | MA       | mast arm                 | Perf                 | perforated                    | Res      | reservation                                 |
| HTCG   | high tension cable guardrail | Matl     | material                 | Per.                 | perimeter                     | Res      | residence                                   |
| Hwy    | highway                      | Max      | maximum                  | Perm                 | permanent                     | Ret      | retaining                                   |
| Hor    | horizontal                   | MC       | meander corner           | PL                   | pipeline                      | Rev      | reverse                                     |
| HBP    | hot bituminous pavement      | Meas     | measure                  | PI                   | place                         | Rt       | right                                       |
| HMA    | hot mix asphalt              | Mdn      | median                   | P&P                  | plan & profile                | R/W      | right of way                                |
| Hyd    | hydrant                      | MD       | median drain             | PL                   | plastic limit                 | Riv      | river                                       |
| Ph     | hydrogen ion content         | MC       | medium curing            | PI or P <sub>L</sub> | plate                         | Rd       | road  |
|        |                              | MGS      | Midwest Guardrail System | Pt                   | point                         | Rdbd     | road bed                                    |
|        |                              | MM       | mile marker              | PE                   | polyethylene                  | Rdwy     | roadway                                     |
| Id     | identification               | MP       | mile post                | PVC                  | polyvinyl chloride            | RWIS     | roadway weather information system          |
| Incl   | inclinometer tube            | Min      | minimum                  | PCC                  | Portland Cement concrete      | Rk       | rock  |
| IMH    | inlet manhole                | Misc     | miscellaneous            | PP                   | power pole                    | Rt       | route                                       |
| ID     | inside diameter              | Mon      | monument                 | Preempt              | preemption                    |          |   |
| Inst   | instrument                   | Mnd      | mound                    | Prefab               | prefabricated                 |          |   |
| Intchg | interchange                  | Mtbl     | mountable                | Prfmd or Pref        | preformed                     |          |   |
| Intmdt | intermediate                 | Mtd      | mounted                  | Prep                 | preperation                   |          |   |
| Intscn | intersection                 | Mtg      | mounting                 | Press.               | pressure                      |          |   |
| Inv    | invert                       | Mk       | muck                     | PRV                  | pressure relief valve         |          |   |
| IP     | iron pipe                    |          |                          | Prestr               | prestressed                   |          |   |
|        |                              |          |                          | Pvt                  | private                       |          |   |
|        |                              |          |                          | PD                   | private drive                 |          |   |
| Jt     | joint                        |          |                          | Prod.                | production/produce            |          |   |
| Jct    | junction                     | Neop     | neoprene                 | Prog                 | programmed                    |          |   |
|        |                              | Ntwk     | network                  | Prop.                | property                      |          |   |
|        |                              | N        | North                    | Prop Ln              | property line                 |          |   |
|        |                              | NE       | North East               | Ppsd                 | proposed                      |          |   |
|        |                              | NW       | North West               | PB                   | pull box                      |          |   |
|        |                              | NB       | Northbound               |                      |                               |          |   |
|        |                              | No. or # | number                   |                      |                               |          |   |

|  |                   |
|--|-------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 08-03-15                                     | General Revisions |
| 04-23-18                                     | General Revisions |
| 12-18-20                                     | General Revisions |
| 08-16-22                                     | General Revisions |



08/16/22

NDDOT ABBREVIATIONS

D-101-3

|            |                                  |        |                                    |
|------------|----------------------------------|--------|------------------------------------|
| Salv       | salvage(d)                       | Tel    | telephone                          |
| San        | sanitary sewer line              | Tel B  | Telephone Booth                    |
| Sec        | section                          | Tel P  | telephone pole                     |
| SL         | section line                     | Tv     | television                         |
| Sep        | separation                       | Temp   | temperature                        |
| Seq        | sequence                         | Temp   | temporary                          |
| Serv       | service                          | TBM    | temporary bench mark               |
| Sht        | sheet                            | T      | thinwall tube sample               |
| Shtng      | sheeting                         | Ts     | topsoil                            |
| Shldr      | shoulder                         | Traf   | traffic                            |
| Sw or Sdwk | sidewalk                         | TSCB   | traffic signal control box         |
| SD         | sight distance                   | Tr     | trail                              |
| SN         | sign number                      | Transf | transformer                        |
| Sig        | signal                           | Trans  | transition                         |
| Sgl        | single                           | TT     | transmission tower                 |
| SRCP       | slotted reinforced concrete pipe | TES    | traversable end section            |
| SC         | slow curing                      | Trans  | transverse                         |
| SS         | slow setting                     | Trtd   | treated                            |
| Sm         | small                            | Trmt   | treatment                          |
| S          | South                            | Qc     | triaxial compression               |
| SE         | South East                       | TERO   | tribal employment rights ordinance |
| SW         | South West                       | Tpl    | triple                             |
| SB         | Southbound                       | Typ    | typical                            |
| Sp         | spaces                           |        |                                    |
| Spcl       | special                          | Qu     | unconfined compressive strength    |
| SA         | special assembly                 | Ugrnd  | underground                        |
| SP         | special provisions               | Util   | utility                            |
| G          | specific gravity                 |        |                                    |
| Spk        | spike                            |        |                                    |
| SB         | split barrel sample              | VG     | valley gutter                      |
| SH         | sprinkler head                   | Vap    | vapor                              |
| SV         | sprinkler valve                  | Vert   | vertical                           |
| Sq         | square                           | VCP    | vitrified clay pipe                |
| Stk        | stake                            | Vol    | volume                             |
| Std        | standard                         | VSFS   | vehicle speed feedback sign        |
| N          | standard penetration test        |        |                                    |
| Std Specs  | standard specifications          | Wkwy   | walkway                            |
| Stm L      | steam line                       | W      | water content                      |
| SEC        | steel encased concrete           | WGV    | water gate valve                   |
| SMA        | stone matrix asphalt             | WL     | water line                         |
| SSD        | stopping sight distance          | WM     | water main                         |
| SD         | storm drain                      | WMV    | water main valve                   |
| St         | street                           | W Mtr  | water meter                        |
| SPP        | structural plate pipe            | WSV    | water service valve                |
| SPPA       | structural plate pipe arch       | WW     | water well                         |
| Str        | structure                        | Wrng   | wearing                            |
| Subd       | subdivision                      | WIM    | weigh in motion                    |
| Sub        | subgrade                         | W      | west                               |
| Sub Prep   | subgrade preparation             | WB     | westbound                          |
| Ss         | subsoil                          | Wrng   | wiring                             |
| SS         | supplement specification         | W/     | with                               |
| Supp       | supplemental                     | W/o    | without                            |
| Surf       | surfacing                        | WC     | witness corner                     |
| Surv       | survey                           |        |                                    |
| Sym        | symmetrical                      |        |                                    |

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
|--|-------------------|
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 09-03-15                                     | General Revisions |
| 04-23-18                                     | General Revisions |
| 12-18-20                                     | General Revisions |
| 08-16-22                                     | General Revisions |



08/16/22

MEASUREMENTS

|          |                          |
|----------|--------------------------|
| ac       | acres                    |
| A        | ampere                   |
| Bd Ft    | board feet               |
| Cd       | candela                  |
| cm       | centimeter               |
| C        | coulomb                  |
| CF       | cubic feet               |
| m3       | cubic meter              |
| m3/s     | cubic meters per second  |
| CY       | cubic yard               |
| CY/mi    | cubic yards per mile     |
| D or Deg | degree                   |
| F        | Fahrenheit               |
| F        | farad                    |
| ft       | feet/foot                |
| Gal      | gallon                   |
| G        | giga                     |
| Ha       | hectare                  |
| H        | henry                    |
| Hz       | hertz                    |
| hr       | hour(s)                  |
| in       | inch                     |
| J        | joule                    |
| K        | kelvin                   |
| kN       | kilo newton              |
| kPa      | kilo pascal              |
| kg       | kilogram                 |
| kg/m3    | kilogram per cubic meter |
| km       | kilometer                |
| K        | Kip(s)                   |
| LF       | linear foot              |
| L        | litre                    |
| Lm       | lumen                    |
| L sum    | lump sum                 |
| Lx       | lux                      |
| M Hr     | man hour                 |
| M        | mega                     |
| m        | meter                    |
| m/s      | meters per second        |
| mi       | mile                     |
| mL       | milliliter               |
| mm       | millimeter               |
| mm/hr    | millimeters per hour     |
| n        | nano                     |
| N        | newton                   |
| Pa       | pascal                   |
| lb       | pounds                   |
| sec      | seconds                  |
| S        | siemens                  |
| SF       | square feet              |
| km2      | square kilometer         |
| m2       | square meter             |
| SY       | square yard              |
| Sta Yd   | station yards            |
| SI       | Systems International    |

|      |               |
|------|---------------|
| T    | tesla         |
| T/mi | tons per mile |
| V    | volt          |
| W    | watt          |
| Wb   | weber         |

SURVEY DESCRIPTIONS

|         |                                 |
|---------|---------------------------------|
| Az      | azimuth                         |
| Bs      | backsight                       |
| Brg     | bearing                         |
| BP Cap  | blue plastic cap                |
| BS      | both sides                      |
| BC      | brass cap                       |
| CS      | curve to spiral                 |
| Eq      | equation                        |
| E       | external of curve               |
| FS      | far side                        |
| FB      | field book                      |
| Fs      | foresight                       |
| Geod    | geodetic                        |
| GIS     | Geographical Information System |
| GPS     | Global Positioning System       |
| HI      | height of instrument            |
| IM      | iron monument                   |
| I Pn    | iron pin                        |
| LS      | Land Surveyor (licensed)        |
| LSIT    | Land Surveyor In Training       |
| L       | length of curve                 |
| LC      | long chord                      |
| LB      | level book                      |
| Mer     | meridian                        |
| M       | mid ordinate of curve           |
| NGS     | National Geodetic Survey        |
| NS      | near side                       |
| Obsn    | observation                     |
| Off Loc | office location                 |
| OP Cap  | orange plastic cap              |
| PK      | Parker-Kalon nail               |
| P Cap   | plastic cap                     |
| PP Cap  | pink plastic cap                |
| PCC     | point of compound curve         |
| PC      | point of curve                  |
| PI      | point of intersection           |
| PRC     | point of reverse curvature      |
| PT      | point of tangent                |
| POC     | point on curve                  |
| POT     | point on tangent                |
| RTP     | random traverse point           |
| Rge     | range                           |
| RP Cap  | red plastic cap                 |
| SC      | spiral to curve                 |
| ST      | spiral to tangent               |
| Sta     | station                         |
| SE      | superelevation                  |
| Tan     | tangent                         |
| T       | tangent (semi)                  |
| TS      | tangent to spiral               |
| Twp     | township                        |
| TB      | transit book                    |
| TP      | traverse point                  |
| TP      | turning point                   |
| USC&G   | US Coast & Geodetic Survey      |
| USGS    | US Geologic Survey              |
| VC      | vertical curve                  |
| WGS     | World Geodetic System           |
| YP Cap  | yellow plastic cap              |
| Z       | zenith                          |

SOIL TYPES

|           |                 |
|-----------|-----------------|
| Cl        | clay            |
| Cl F      | clay fill       |
| Cl Hvy    | clay heavy      |
| Cl Lm     | clay loam       |
| Co S      | coal slack      |
| C Gr      | coarse gravel   |
| CS        | coarse sand     |
| FS        | fine sand       |
| Gr        | gravel          |
| Lig Co    | lignite coal    |
| Lig Sl    | lignite slack   |
| Lm        | loam            |
| Rk        | rock            |
| Sd        | sand            |
| Sdy Cl    | sandy clay      |
| Sdy Cl Lm | sandy clay loam |
| Sdy Fl    | sandy fill      |
| Sdy Lm    | sandy loam      |
| Sc        | scoria          |
| Sh        | shale           |
| Si Cl     | silt clay       |
| Si Cl Lm  | silty clay loam |
| Si Lm     | silty loam      |

|  |   |
|--|---|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
| 07-01-14                                     |   |
| REVISIONS                                    |   |
| DATE   | CHANGE                                  |
| 12-18-20                                     | Sheet Added<br>- Continued from D-101-3 |



12 18 2020



NDDOT UTILITY COMPANY AND ORGANIZATION ABBREVIATIONS

D-101-10

|                    |   |                    |   |                    |   |
|--------------------|---|--------------------|---|--------------------|---|
| 702COM             | 702 Communications                        | GT PLNS NAT GAS    | Great Plains Natural Gas Company                  | RED RIV COMM       | Red River Rural Communications              |
| ACCENT             | Accent Communications                     | HALS TEL           | Halstad Telephone Company                         | RESVTN TEL         | Reservation Telephone                       |
| AGASSIZ WU         | Agassiz Water Users Incorporated          | IDEA1              | Idea1   | ROBRTS TEL         | Roberts Company Telephone                   |
| AGC                | Associated General Contractors of America | INT-COMM TEL       | Inter-Community Telephone Company                 | R-RIDER ELEC       | Roughrider Electric Cooperative             |
| ALL PL             | Alliance Pipeline                         | KANEB PL           | Kaneb Pipeline Company                            | RRVW               | Red River Valley & Western Railroad         |
| ALL SEAS WU        | All Seasons Water Users Association       | KEM ELEC           | Kem Electric Cooperative Incorporated             | S CENT REG WD      | South Central Regional Water District       |
| AMOCO PI           | Amoco Pipeline Company                    | KOCH GATH SYS      | Koch Gathering Systems Incorporated               | S E W U            | South East Water Users Incorporated         |
| AMRDA HESS         | Amerada Hess Corporation                  | LKHD PL            | Lakehead Pipeline Company                         | SCOTT CABLE        | Scott Cable Television Dickinson            |
| AT&T               | AT&T Corporation                          | LNGDN RWU          | Langdon Rural Water Users Incorporated            | SHERDN ELEC        | Sheridan Electric Cooperative               |
| B PAW              | Bear Paw Energy Incorporated              | LWR YELL R ELEC    | Lower Yellowstone Rural Electric                  | SHEYN VLY ELEC     | Sheyenne Valley Electric Cooperative        |
| BAKER ELEC         | Baker Electric                            | MCKNZ CON          | McKenzie Consolidated Telcom                      | SKYTECH            | Skyland Technologies Incorporated           |
| BASIN ELEC         | Basin Electric Cooperative Incorporated   | MCKNZ ELEC         | McKenzie Electric Cooperative                     | SLOPE ELEC         | Slope Electric Cooperative Incorporated     |
| BEK TEL            | Bek Communications Cooperative            | MCKNZ WRD          | McKenzie County Water Resource District           | SOURIS RIV TELCOM  | Souris River Telecommunications             |
| BELLE PL           | Belle Fourche Pipeline Company            | MCLEOD             | McLeod USA  | ST WAT COMM        | State Water Commission                      |
| BLM                | Bureau of Land Management                 | MCLN ELEC          | McLean Electric Cooperative                       | STATE LN WATER     | State Line Water Cooperative                |
| BNSF               | Burlington Northern Santa Fe Railway      | MCLN-SHRDN R WAT   | McLean-Sheridan Rural Water                       | STER ENG           | Sterling Energy                             |
| BOEING             | Boeing                                    | MDU                | Montana-dakota Utilities                          | STUT RWU           | Stutsman Rural Water Users                  |
| BRNS RWD           | Barnes Rural Water District               | MIDCO              | MidContinent Communications                       | SW PL PRJ          | Southwest Pipeline Project                  |
| BURK-DIV ELEC      | Burke-Divide Electric Cooperative         | MIDSTATE TEL       | Midstate Telephone Company                        | T M C              | Turtle Mountain Communications              |
| BURL WU            | Burleigh Water Users                      | MINOT CABLE        | Minot Cable Television                            | TCI                | TCI of North Dakota                         |
| CABLE ONE          | Cable One                                 | MINOT TEL          | Minot Telephone Company                           | TESORO HGH PLNS PL | Tesoro High Plains Pipeline                 |
| CABLE SERV         | Cable Services                            | MISS VALL COMM     | Missouri Valley Communications                    | TRI-CNTY WU        | Tri-County Water Users Incorporated         |
| CAP ELEC           | Capital Electric Cooperative Incorporat   | MISS W W S         | Missouri West Water System                        | TRL CO RWU         | Traill County Rural Water Users             |
| CASS CO ELEC       | Cass County Electric Cooperative          | MNKOTA PWR         | Minnkota Power                                    | UNTD TEL           | United Telephone                            |
| CASS RWU           | Cass Rural Water Users Incorporated       | MOR-GRAN-SOU ELEC  | Mor-gran-sou Electric Cooperative                 | UPPR SOUR WUA      | Upper Souris Water Users Association        |
| CAV ELEC           | Cavalier Rural Electric Cooperative       | MOUNT-WILLI ELEC   | Mountrail-williams Electric Cooperative           | US SPRINT          | U.S. Sprint                                 |
| CBLCOM             | Cablecom Of Fargo                         | MRE LBTY TEL       | Moore & Liberty Telephone                         | USAF MSL CABLE     | U.S.A.F. Missile Cable                      |
| CENEX PL           | Cenex Pipeline                            | MUNICIPAL          | City Water And Sewer                              | USFWS              | US Fish and Wildlife Service                |
| CENT PL WATER DIST | Central Pipe Line Water District          | MUNICIPAL          | City Of '.....'                                   | USW COMM           | U.S. West Communications                    |
| CENT PWR ELEC      | Central Power Electric Cooperative        | N CENT ELEC        | North Central Electric Cooperative                | VRNDRY ELEC        | Verendrye Electric Cooperative              |
| CENTURYLINK        | CenturyLink                               | N VALL W DIST      | North Valley Water District                       | W RIV TEL          | West River Telephone Incorporated           |
| COE                | Corps of Engineers                        | ND PKS & REC       | North Dakota Parks And Recreation                 | WAPA               | Western Area Power Administration           |
| CONS TEL           | Consolidated Telephone                    | ND TEL             | North Dakota Telephone Company                    | WAWSA              | Western Area Water Supply Authority         |
| CONT RES           | Continental Resource Inc                  | NDDOT              | North Dakota Department of Transportation         | WEB                | W. E. B. Water Development Association      |
| CPR                | Canadian Pacific Railway                  | NDSU SOIL SCI DEPT | NDSU Soil Science Department                      | WILLI RWA          | Williams Rural Water Association            |
| D O E              | Department Of Energy                      | NEMONT TEL         | Nemont Telephone                                  | WILSTN BAS PL      | Williston Basin Interstate Pipeline Company |
| DAK CARR           | Dakota Carrier Network                    | NODAK R ELEC       | Nodak Rural Electric Cooperative                  | WLSH RWD           | Walsh Water Rural Water District            |
| DAK CENT TEL       | Dakota Central Telephone                  | NOON FRMS TEL      | Noonan Farmers Telephone Company                  | WOLVRTN TEL        | Wolverton Telephone                         |
| DAK RWD            | Dakota Rural Water District               | NPR                | Northern Plains Railroad                          | XLENER             | Xcel Energy                                 |
| DGC                | Dakota Gasification Company               | NSP                | Northern States Power                             | YSVR               | Yellowstone Valley Railroad                 |
| DICKEY R NET       | Dickey Rural Networks                     | NTH PRAIR RW       | Northern Prairie Rural Water Association          |                    |   |
| DICKEY RWU         | Dickey Rural Water Users Association      | NTHN BRDR PL       | Northern Border Pipeline                          |                    |   |
| DICKEY TEL         | Dickey Telephone                          | NTHN PLNS ELEC     | Northern Plains Electric Cooperative Incorporated |                    |   |
| DNRR               | Dakota Northern Railroad                  | NTHWSTRN REF       | Northwestern Refinery Company                     |                    |   |
| DOME PL            | Dome Pipeline Company                     | NW COMM            | Northwest Communication Cooperation               |                    |   |
| DVELEC             | Dakota Valley Electric Cooperative        | NWRWD              | Northwest Rural Water District                    |                    |   |
| DVMW               | Dakota, Missouri Valley & Western         | ONEOK              | Oneok gas   |                    |   |
| ENBRDG             | Enbridge Pipelines Incorporated           | OSHA               | Occupational Safety and Health Administration     |                    |   |
| ENVENTIS           | Enventis Telephone                        | OTTR TL PWR        | Otter Tail Power Company                          |                    |   |
| EQUINOR            | Equinor Pipeline                          | PAAP               | Plains All American Pipeline                      |                    |   |
| FALK MNG           | Falkirk Mining Company                    | P L E M            | Prairielands Energy Marketing                     |                    |   |
| FHWA               | Federal Highway Administration            | POLAR COM          | Polar Communications                              |                    |   |
| G FKS-TRL WD       | Grand Forks-traill Water District         | PVT ELEC           | Private Electric                                  |                    |   |
| GETTY TRD & TRAN   | Getty Trading & Transportation            | QWEST              | Qwest Communications                              |                    |   |
| GLDN W ELEC        | Golden West Electric Cooperative          | R&T W SUPPLY       | R & T Water Supply Association                    |                    |   |
| GRGS CO TEL        | Griggs County Telephone                   |                    |   |                    |   |
| GTR RAMSEY WD      | Greater Ramsey Water District             |                    |   |                    |   |

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
|--|-------------------|
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 04-23-18                                     | General Revisions |
| 09-20-18                                     | General Revisions |
| 12-10-20                                     | General Revisions |
| 08-16-22                                     | General Revisions |


























08/16/22

















LINE STYLES









D-101-20

Existing Topography























|   |                                    |
|---|------------------------------------|
|    | Existing Ground Void               |
|    | Existing Cemetary Boundary         |
|    | Existing Box Culvert Bridge        |
|    | Existing Concrete Surface          |
|    | Existing Drainage Structure        |
|    | Existing Gravel Surface            |
|    | Existing Riprap                    |
|    | Existing Dirt Surface              |
|    | Existing Asphalt Surface           |
|    | Existing Tie Point Line            |
|  | Existing Railroad Centerline       |
|  | Existing Guardrail Cable           |
|  | Existing Guardrail Metal           |
|  | Existing Edge of Water             |
|  | Existing Fence                     |
|  | Existing Railroad                  |
|  | Existing Field Line                |
|  | Exst Flow                          |
|  | Existing Curb                      |
|  | Existing Valley Gutter             |
|  | Existing Driveway Gutter           |
|  | Existing Curb and Gutter           |
|  | Existing Mountable Curb and Gutter |

|  |  |
|--|--|
|    | Existing 3-Cable w Posts                         |
|    | Site Boundary                                    |
|    | Existing Berm, Dike, Pit, or Earth Dam           |
|    | Existing Ditch Block                             |
|    | Existing Tree Boundary                           |
|    | Existing Brush or Shrub Boundary                 |
|    | Existing Retaining Wall                          |
|    | Existing Planter or Wall                         |
|    | Existing W-Beam Guardrail with Posts             |
|    | Existing Railroad Switch                         |
|    | Gravel Pit - Borrow Area                         |
|  | Existing Wet Area-Vegetation Break               |
|  | Existing High Tension Cable Guardrail            |
|  | Existing High Tension Cable Guardrail with Posts |





Proposed Topography

|  |   |
|--|---|
|  | 3-Cable w Posts                         |
|  | Flow                                    |
|  | Fence                                   |
|  | Remove Line                             |
|  | Wall                                    |
|  | Retaining Wall (Plan View)              |
|  | W-Beam w Posts                          |
|  | High Tension Cable Guardrail with Posts |










Existing Utilities

|   |  |
|---|--|
|    | Existing Electrical                        |
|    | Existing Fiber Optic Line                  |
|    | Existing TV Fiber Optic                    |
|    | Existing Gas Pipe                          |
|    | Existing Overhead Utility Line             |
|    | Existing Power                             |
|    | Existing Fuel Pipeline                     |
|    | Existing Undefined Above Ground Pipe Line  |
|    | Existing Sanitary Sewer                    |
|    | Existing Sanitary Force Main               |
|  | Existing Storm Drain                       |
|  | Existing Storm Drain Force Main            |
|  | Existing Culvert                           |
|  | Existing Telephone Line                    |
|  | Existing TV Line                           |
|  | Existing Water or Steam Line               |
|  | Existing Under Drain                       |
|  | Existing Slotted Drain                     |
|  | Existing Conduit                           |
|  | Existing Conductor                         |
|  | Existing Down Guy Wire Down Guy            |
|  | Existing Underground Vault or Lift Station |




Proposed Utilities


|   |                          |
|---|--------------------------|
|  | 24 Inch Pipe             |
|  | Reinforced Concrete Pipe |
|  | Under Drain              |
|  | Edge Drain               |

Traffic Utilities

|   |                                     |
|---|-------------------------------------|
|    | Conductor                           |
|    | Fiber Optic                         |
|    | Existing Loop Detector              |
|    | Existing Double Micro Loop Detector |
|  | Micro Loop Detector Double          |
|  | Existing Micro Loop Detector        |
|  | Micro Loop Detector                 |
|  | Signal Head with Mast Arm           |
|  | Existing Signal Head with Mast Arm  |

Sign Structures














|   |   |
|---|---|
|  | Existing Overhead Sign Structure            |
|  | Existing Overhead Sign Structure Cantilever |
|  | Overhead Sign Structure Cantilever          |

|  |   |   |
|--|---|---|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |  |
| 07-01-14<br>REVISIONS                        |   |   |
| DATE   | CHANGE  |   |
| 09-23-16<br>12-18-20                         | Added and Revised Items,<br>Organized by Functional Groups<br>General Revisions |   |
|  |   | 12 18 2020  |










LINE STYLES

D-101-21









Right Of Way

|   |                                       |
|---|---------------------------------------|
|    | Easement                              |
|    | Existing Easement                     |
|    | Right of Way                          |
|    | Existing Right of Way                 |
|    | Existing Right of Way Railroad        |
|    | Existing Right of Way Not State Owned |
|    | Existing Government Lot Line          |
|    | Existing Adjacent Block Lines         |
|    | Existing Adjacent Lot Lines           |
|    | Existing Adjacent Property Line       |
|  | Existing Adjacent Subdivision Lines   |
|  | Sight Distance Triangle Line          |
|  | Dimension Leader                      |







Boundary Control



|   |  |
|---|--|
|  | Existing City Corporate Limits or Reservation Boundary |
|  | Existing State or International Line                   |
|  | Existing Township                                      |
|  | Existing County  |
|  | Existing Section Line                                  |
|  | Existing Quarter Section Line                          |
|  | Existing Sixteenth Section Line                        |
|  | Existing Centerline                                    |
|  | Tangent Line   |

Cross Sections and Typicals



|  |   |
|--|---|
|  | Existing Ground                               |
|  | Existing Topsoil (Cross Section View)         |
|  | Existing Ground Void (Not Surveyed)           |
|  | Existing Concrete                             |
|  | Existing Aggregate (Cross Section View)       |
|  | Existing Curb and Gutter (Cross Section View) |
|  | Existing Asphalt (Cross Section View)         |
|  | Existing Reinforcement Rebar                  |

Geotechnical



|  |                           |
|--|---------------------------|
|    | Geotextile Fabric Type D  |
|   | Geogrid                   |
|  | Geotextile Fabric Type R  |
|  | Geotextile Fabric Type R1 |
|  | Geotextile Fabric Type RR |
|  | Geotextile Fabric Type S  |

|  |                        |
|--|------------------------|
|  | Subgrade Reinforcement |
|  | Failure Line           |







Countours

|  |                      |
|--|----------------------|
|  | Depression Contours  |
|  | Supplemental Contour |





Profile

|  |                                 |
|--|---------------------------------|
|  | Subgrade, Subcut or Ditch Grade |
|  | Topsoil Profile                 |










Striping

|   |  |
|---|--|
|  | Centerline Pavement Marking              |
|  | Barrier with Centerline Pavement Marking |
|  | Barrier Pavement Marking                 |
|  | Stripe 4 IN Dotted Extension White       |
|  | Stripe 8 IN Dotted Extension White       |
|  | Stripe 8 IN Lane Drop                    |








Pavement Joints

|   |   |
|---|---|
|    | Doweled Joint                           |
|    | Tie Bar 30 Inch 4 Foot Center to Center |
|   | Tie Bar 18 Inch 3 Foot Center to Center |
|  | Tie Bar at Random Spacing               |






Bridge Details

|   |                            |
|---|----------------------------|
|  | Small Hidden Object        |
|  | Large Hidden Object        |
|  | Phantom Object             |
|  | Existing Conditions Object |
|  | Centerline Main            |
|  | Centerline Secondary       |
|  | Excavation Limits          |
|  | Proposed Ground            |
|  | Sheet Piling               |

Erosion Control

|   |                                 |
|---|---------------------------------|
|  | Limits of Const Transition Line |
|  | Bale Check                      |
|  | Rock Check                      |
|  | Floating Silt Curtain           |
|  | Silt Fence                      |
|  | Excavation Limits               |
|  | Fiber Rolls                     |

Environmental

|   |                                 |
|---|---------------------------------|
|    | Wetland Mitigation              |
|   | Existing Wetland Easement USFWS |
|  | Existing Wetland Jurisdictional |
|  | Existing Wetland                |
|  | Tree Row                        |

NORTH DAKOTA  
DEPARTMENT OF TRANSPORTATION

07-01-14

REVISIONS

| DATE     | CHANGE  |
|----------|---|
| 09-23-16 | Added and Revised Items,<br>Organized by Functional Groups<br>General Revisions |
| 12-18-20 |   |

KIRK J. HOFF

REGISTERED

PROFESSIONAL

PE-4683

ENGINEER

NORTH DAKOTA

12 18 2020


SYMBOLS

D-101-30


 North Arrow (Half Scale)


 Alignment Data Point

 Alignment Monument


 Spot Elevation

 Existing Miscellaneous Spot

 Existing Access Control Arrow

 Existing Benchmark

 Reset USGS Marker

 Iron Monument Found

 Iron Pin R/W Monument

 Property Corner

 Iron Pin Reference Monument


   Right of Way Marker (Exst, Ppsd, Reset)

 Existing Federal Reference Corner

    Existing Section Corner (Full, Quarter, Sixteenth, Meander)


 Existing Witness Corner


   Existing Control Point (CP, GPS-RTK, TRI)


 Existing Traverse PI Aerial Panel


 Existing Reference Marker Point NGS

 Existing EFB Misc

 Existing Bush or Shrub


 Existing Large Evergreen Tree

 Existing Small Evergreen Tree

 Existing Large Tree

 Existing Small Tree

 Existing Tree Trunk

 Cairn or Stone Circle


 Existing Artifact


 Existing Satellite Dish

 Existing Weather Station

 Existing Windmill or Tower


 Reinforced Pavement


 Continuous Split Barrel Sample

 Flight Auger Sample

 Split Barrel Sample

 Thinwall Tube Sample

 Standard Penetration Test

 Inclinometer Tube

 Excavation Unit

 Existing Ground Water Well Bore Hole

|  |                   |
|--|-------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 12-18-20                                     | General Revisions |

KIRK J. HOFF

REGISTERED

PROFESSIONAL

PE-4683

ENGINEER

NORTH DAKOTA


12 18 2020

SYMBOLS

D-101-31

|   |  |   |                                      |
|---|--|---|--------------------------------------|
|    | Flexible Delineator  |    | Highway Sign (Exst, Ppsd)            |
|    | Flexible Delineator Type A (Exst, Ppsd)  |    | Mile Post Type A (Exst-Ppsd-Reset)   |
|    | Flexible Delineator Type B (Exst, Ppsd)  |    | Mile Post Type B (Exst, Ppsd)        |
|    | Flexible Delineator Type C (Exst, Ppsd)  |    | Mile Post Type C (Exst, Ppsd)        |
|    | Flexible Delineator Type D (Exst, Ppsd)  |    | Object Marker Type I (Exst, Ppsd)    |
|    | Flexible Delineator Type E (Exst, Ppsd)  |    | Object Marker Type II (Exst, Ppsd)   |
|    | Delineator Type A (Exst, Ppsd, Diamond Grade-Reset)  |    | Object Marker Type III (Exst, Ppsd)  |
|    | Delineator Type B (Exst, Ppsd, Diamond Grade-Reset)  |    | Existing Reference Marker            |
|    | Delineator Type C (Exst, Ppsd, Diamond Grade)  |    | Road Closure Gate 18 Ft (Exst, Ppsd) |
|    | Delineator Type D (Exst, Ppsd, Diamond Grade)  |    | Road Closure Gate 28 Ft (Exst, Ppsd) |
|    | Delineator Type E (Exst, Ppsd, Diamond Grade)  |    | Road Closure Gate 40 Ft (Exst, Ppsd) |
|   | Barricade (Type I, Type II, Type III)  |   | Existing Railroad Battery Box        |
|  | Arrow Panel (Caution Mode, Double Direction, Left Directional, Right Directional, Sequencing, Truck Mounted) |  | Existing RR Profile Spot             |
|  | Attenuation Device   |  | Existing Railroad Crossbuck          |
|  | Truck Mounted Attenuator   |  | Existing Railroad Frog               |
|  | Delineator Drums   |  | Existing Mailbox (Private, Federal)  |
|  | Flagger  |   |                                      |
|  | Tubular Marker   |   |                                      |
|  | Traffic Cone   |   |                                      |
|  | Back to Back Vertical Panel Sign   |   |                                      |

















































































|  |                   |
|--|-------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 12-18-20                                     | General Revisions |



12 18 2020

SYMBOLS

D-101-32


|   |   |   |   |  |   |   |   |   |  |
|---|---|---|---|--|---|---|---|---|--|
|    | Existing Luminaire  |    |    | High Mast Light Standard 3 Luminaire (Exst, Ppsd)  |  | Existing Traffic Signal Standard  |   |   |  |
|    | Luminaire LED   |    |    | High Mast Light Standard 4 Luminaire (Exst, Ppsd)  |  |  |  | Pull Box (Exst-Ppsd-Undefined)  |  |
|    | Existing Light Standard Luminaire                             |    |    | High Mast Light Standard 5 Luminaire (Exst, Ppsd)  |  |  |   | Intelligent Transportation Pull Box (Exst, Ppsd)                                    |  |
|    | Relocate Light Standard                                       |    |    | High Mast Light Standard 6 Luminaire (Exst, Ppsd)  |   |  |  | Transformer (Exst, Ppsd)  |  |
|    | Light Standard Light LED Luminaire                            |    |    | High Mast Light Standard 7 Luminaire (Exst, Ppsd)  |  |  |  | Power Pole (Exst-Ppsd-with Transformer)   |  |
|    | Light Standard 35 Watt High Pressure Sodium Vapor Luminaire   |    |    | High Mast Light Standard 8 Luminaire (Exst, Ppsd)  |   |  |  | Wood Pole (Exst, Ppsd)  |  |
|    | Light Standard 50 Watt High Pressure Sodium Vapor Luminaire   |    |    | High Mast Light Standard 9 Luminaire (Exst, Ppsd)  |   |  |  | Pedestrian Push Button Post (Exst, Ppsd)  |  |
|    | Light Standard 70 Watt High Pressure Sodium Vapor Luminaire   |    |    | High Mast Light Standard 10 Luminaire (Exst, Ppsd) |   |   |  | Existing Pole   |  |
|    | Light Standard 100 Watt High Pressure Sodium Vapor Luminaire  |    |    | Overhead Sign Structure Load Center (Exst, Ppsd)   |   |   |  | Existing Telephone Pole   |  |
|    | Light Standard 150 Watt High Pressure Sodium Vapor Luminaire  |    |    | Traffic Signal Controller (Exst, Ppsd)             |   |   |  | Existing Post   |  |
|    | Light Standard 200 Watt High Pressure Sodium Vapor Luminaire  |    |    | Pad Mounted Traffic Signal Controller (Exst, Ppsd) |  |  |  |  | Connection Conductor (Ground, Neutral, Phase 1, Phase 2) |
|  | Light Standard 250 Watt High Pressure Sodium Vapor Luminaire  |  |  | Flashing Beacon (Exst, Ppsd)                       |   |   |   |   |  |
|  | Light Standard 310 Watt High Pressure Sodium Vapor Luminaire  |  |  | Concrete Foundation (Exst, Ppsd)                   |   |   |   |   |  |
|  | Light Standard 400 Watt High Pressure Sodium Vapor Luminaire  |  |  | Pipe Mounted Flasher (Exst, Ppsd)                  |   |   |   |   |  |
|  | Light Standard 700 Watt High Pressure Sodium Vapor Luminaire  |  |  | Pad Mounted Feed Point (Exst, Ppsd)                |   |   |   |   |  |
|  | Light Standard 1000 Watt High Pressure Sodium Vapor Luminaire |  |  | Pipe Mounted Feed Point with Pad (Exst, Ppsd)      |   |   |   |   |  |
|  | Emergency Vehicle Detector                                    |  |  | Pole Mounted Feed Point (Exst, Ppsd)               |   |   |   |   |  |
|  | Video Detection Camera  |  |  | Junction Box (Exst, Ppsd)                          |   |   |   |   |  |
|   |   |  |   | Existing Pedestrian Head with Number               |   |   |   |   |  |
|   |   |  |   | Existing Signal Head                               |   |   |   |   |  |
|   |   |   |  | Pole Mounted Head                                  |   |   |   |   |  |
|   |   |  |   | Existing Lighting Standard Pole                    |   |   |   |   |  |

|  |                   |
|--|-------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
| 07-01-14                                     |                   |
| REVISIONS                                    |                   |
| DATE   | CHANGE            |
| 12-18-20                                     | General Revisions |

KIRK J. HOFF  
REGISTERED  
PROFESSIONAL

Kirk J Hoff

|  |                   |
|--|-------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                   |
| 07-01-14<br>REVISIONS                        |                   |
| DATE   | CHANGE            |
| 12-18-20                                     | General Revisions |



12 18 2020

SYMBOLS

D-101-33




|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  | Existing Manhole (Electrical, Gas, Telephone)  |  | Cap or Stub<br>Exst Gas, Exst Sanitary, Exst Storm Drain, Ppsd Storm Drain, Exst Water           |
|  |  |  | Water Manhole (Exst, Exst with Valve)  |  | Existing Pedestal<br>Electrical, Telephone, Fiber Optic Telephone, TV, Fiber Optic TV, Undefined |
|  |  |  | Sanitary Sewer Manhole (Exst, Ppsd, Exst with Valve)   |  | Existing Pipe Vent<br>Gas, Fuel, Sanitary, Storm Drain, Water, Undefined                         |
|  |  |  | Sanitary Force Main Manhole (Exst, Ppsd, Exst with Valve)  |  | Valve<br>Exst Gas, Exst Water, Ppsd Water, Exst Undefined  |
|  |  |  | Storm Drain Manhole (Exst, Ppsd, Exst with Inlet, Ppsd with Inlet)                                 |  | Pump<br>Sanitary, Storm Drain, Exst Water  |
|  |  |  | Force Main Storm Drain Manhole (Exst, Exst with Valve)   |  | Corrugated Metal End Section (18, 24, 30, 36, 42, 48, 54, 60 Inch)                               |
|  |  |  | Manhole (Ppsd, Ppsd 48 Inch, Exst Undefined)   |  | Reinforced Concrete End Section (18, 24, 30, 36, 42, 48, 54, 60 Inch)                            |
|  |  |  | Existing Water Appurtenance  |  | Existing Utility Marker  |
|  |  |  | Sprinkler Head (Exst, Ppsd)  |  | Existing Meter   |
|  |  |  | Fire Hydrant (Exst, Ppsd)  |  | Existing Fuel Dispensers   |
|  |  |  | Cleanout (Exst Sanitary, Underdrain)   |  | Existing Fuel Filler Pipes   |
|  |  |  | Existing Catch Basin Inlet (Round, Square)   |  | Existing Fuel Leak Sensors   |
|  |  |  | Existing Curb Inlet (Round, Square)  |  |  |
|  |  |  | Existing Slotted Reinforced Concrete Pipe  |  |  |
|  |  |  | Catch Basin (Riser 30 Inch, Beehive, Type A)   |  |  |
|  |  |  | Inlet Mountable Curb (Type A, Type B)  |  |  |
|  |  |  | Inlet Saddle Base (Type 1, Type 2)   |  |  |
|  |  |  | Inlet Special (Catch Basin, Type 1, Type A)  |  |  |
|  |  |  | Inlet (Tee, Type 1, Type 2, Type 2 Double)   |  |  |
|  |  |  | Median Drain   |  |  |
|  |  |  | Headwall (Exst, Ppsd, Ppsd Single with Vegetation Barrier,<br>Ppsd Double with Vegetation Barrier) |  |  |

|  |   |
|--|---|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
| 07-01-14                                     |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 12-18-20                                     | General Revisions<br>Sheet added<br>- Continued from D-101-32 |

KIRK J. HOFF  
REGISTERED  
PROFESSIONAL  
PE-4683  
ENGINEER  
NORTH DAKOTA  
12 18 2020

Perforated Tube

- Notes:
1. Torque slip base bolts as specified by manufacturer.
  2. Use anchor with 43.9 KSI yield strength and 59.3 KSI tensile strength.
  3. Provide 4" vertical clearance for anchor or breakaway base. Measure the 4"x60" measurement above and below post location and back and ahead of post.
  4. In concrete sidewalk, use same anchor without wings.
  5. Provide more than 7' between the first and fourth posts of a four post sign.





| Telescoping Perforated Tube |               |                       |                 |                       |           |                                   |
|-----------------------------|---------------|-----------------------|-----------------|-----------------------|-----------|-----------------------------------|
| Number of Posts             | Post Size in. | Wall Thick-ness Gauge | Sleeve Size in. | Wall Thick-ness Gauge | Slip Base | Anchor Size without Slip Base in. |
| 1                           | 2             | 12                    |                 |                       | No        | 2 1/4                             |
| 1                           | 2 1/4         | 12                    |                 |                       | No        | 2 1/2                             |
| 1                           | 2 1/2         | 12                    |                 |                       | (A)       | 3                                 |
| 1                           | 2 1/2         | 10                    |                 |                       | Yes       |                                   |
| 1                           | 2 1/4         | 12                    | 2               | 12                    | Yes       |                                   |
| 1                           | 2 1/2         | 12                    | 2 1/4           | 12                    | Yes       |                                   |
| 2                           | 2             | 12                    |                 |                       | No        | 2 1/4                             |
| 2                           | 2 1/4         | 12                    |                 |                       | No        | 2 1/2                             |
| 2                           | 2 1/2         | 12                    |                 |                       | Yes       |                                   |
| 2                           | 2 1/2         | 12                    |                 |                       | Yes       |                                   |
| 2                           | 2 1/4         | 10                    | 2               | 12                    | Yes       |                                   |
| 2                           | 2 1/2         | 12                    | 2 1/4           | 12                    | Yes       |                                   |
| 3 & 4                       | 2 1/2         | 12                    |                 |                       | Yes       |                                   |
| 3 & 4                       | 2 1/2         | 10                    |                 |                       | Yes       |                                   |
| 3 & 4                       | 2 1/2         | 12                    | 2 1/4           | 12                    | Yes       |                                   |
| 3 & 4                       | 2 1/4         | 12                    | 2               | 12                    | Yes       |                                   |
| 3 & 4                       | 2 1/2         | 10                    | 2 3/16          | 10                    | Yes       |                                   |

| Properties of Telescoping Perforated Tube |                    |                     |                      |                                    |                                  |                                  |
|---|--------------------|---------------------|----------------------|------------------------------------|----------------------------------|----------------------------------|
| Tube Size in.                             | Wall Thickness in. | U.S. Standard Gauge | Weight per Foot lbs. | Moment of Inertia in. <sup>4</sup> | Cross Sec. Area in. <sup>2</sup> | Section Modulus in. <sup>3</sup> |
| 1 1/2 x 1 1/2                             | 0.105              | 12                  | 1.702                | 0.129                              | 0.380                            | 0.172                            |
| 2 x 2                                     | 0.105              | 12                  | 2.416                | 0.372                              | 0.590                            | 0.372                            |
| 2 1/4 x 2 1/4                             | 0.105              | 12                  | 2.773                | 0.561                              | 0.695                            | 0.499                            |
| 2 3/8 x 2 3/8                             | 0.135              | 10                  | 3.432                | 0.605                              | 0.841                            | 0.590                            |
| 2 1/2 x 2 1/2                             | 0.105              | 12                  | 3.141                | 0.804                              | 0.803                            | 0.643                            |
| 2 1/2 x 2 1/2                             | 0.135              | 10                  | 4.006                | 0.979                              | 1.010                            | 0.785                            |

| Top Post Receiver Data Table |         |        |         |         |          |        |
|------------------------------|---------|--------|---------|---------|----------|--------|
| Square Post Sizes (B)        | A       | B      | C       | D       | E        | F      |
| 2 3/16"x10 ga.               | 1 5/16" | 2 1/2" | 3 1/2"  | 2 5/32" | 1 33/64" | 1 7/8" |
| 2 1/2"x10 ga.                | 1 3/32" | 2 1/2" | 3 5/16" | 5/8"    | 1 21/32" | 1 3/4" |






- (A) Use breakaway base when support is placed in weak soils. Engineer determines if soils are weak.
- (B) For additional wind load, insert the 2 3/8"x10 ga. into 2 1/2"x10 ga.



| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   | This document was originally<br>issued and sealed by<br><br>Kirk J Hoff,<br><br>Registration Number<br>PE- 4683,<br><br>on 10/03/19 and the original<br>document is stored at the<br>North Dakota Department<br>of Transportation |
|--|---|---|
| 2-28-14                                      |   |   |
| REVISIONS                                    |   |   |
| DATE   | CHANGE  |   |
| 9-27-17<br>10-03-19                          | Updated to active voice<br>New Design Engr PE Stamp |   |



U-Channel Post



Alternate A Steps of Installation:


- a) Drive anchor unit to within 12" of ground level.  
b) Establish proper assembly by lining up bottom hole of retainer strap with 6th hole from the top of the anchor unit.  
c) Assemble strap to back of anchor unit using 5/16"x2" bolt, lock washer and nut.  
d) Rotate strap 90° to left.
- a) Drive anchor unit to 4" above ground.  
b) Rotate strap to vertical position.
- a) Place 5/16"x2" bolt, lock washer and nut in bottom of sign post to facilitate alignment of sign post with proper hole in anchor unit.  
b) Alternately tighten two connector bolts.
- Complete assembly by tightening 5/16"x2" bolt (this fastens sign post to retainer strap).
- Properly nest base post, strap, and sign post. Proper nesting occurs when all flat surfaces of the base post, strap, and sign post at the bolts have full contact across the entire width.

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
|--|---|
| 2-28-14                                      |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 9-27-17<br>10-03-19                          | Updated to active voice<br>New Design Engr PE Stamp |


This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 10/03/19 and the original document is stored at the  
North Dakota Department  
of Transportation

CONSTRUCTION SIGN DETAILS  
TERMINAL AND GUIDE SIGNS


D-704-9




G20-1-60  
Legend: black (non-refl)  
Background: orange




G20-50a-72  
Legend: black (non-refl)  
Background: orange




E5-1(L or R)-48  
Legend: white  
Background: green (orange optional)




E5-1-48




G20-1b-60  
Legend: black (non-refl)  
Background: orange




G20-52a-72  
Legend: black (non-refl)  
Background: orange




M4-8-36  
Legend: black (non-refl)  
Background: orange




G20-50a-72  
G20-52a-72




G20-2-48  
Legend: black (non-refl)  
Background: orange




G20-55-96  
Legend: black (non-refl)  
Background: orange



M4-9(L or R)-30  
Right or Left



M4-9(L or R)-30  
Advanced Right or Left




M4-9-30  
Straight

ARROW DETAILS






NOTES:  
(A) Arrow may be right or left of the legend to indicate construction to the right or left.

|  |   |
|--|---|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
| 8-13-13                                      |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 8-17-17<br>10-03-19                          | Added sign & background color<br>New Design Engineer PE Stamp |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 10/03/19 and the original document is stored at the  
North Dakota Department  
of Transportation



M4-9(L or R)-30 &  
M4-9-30  
Legend: black (non-refl)  
Background: orange



|  |   |
|--|---|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
| 8-13-13                                      |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 8-17-17<br>10-03-19                          | Revised sign number<br>New Design Engineer PE Stamp |


This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683 ,  
on 10/03/19 and the original document is stored at the  
North Dakota Department  
of Transportation

## CONSTRUCTION SIGN DETAILS


### WARNING SIGNS



Legend: black (non-refl)  
Background: orange




Legend: black (non-refl)  
Background: orange




Legend: black (non-refl)  
Background: orange



Legend: black (non-refl)  
Background: orange




Legend: black (non-refl)  
Background: orange



Legend: black (non-refl)  
Background: orange



Legend: black (non-refl)  
Background: orange



Legend: black (non-refl)  
Background: orange

## \* DISTANCE MESSAGES




## ARROW DETAILS

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE-4683,  
on 10/03/19 and the original document is stored at the  
North Dakota Department  
of Transportation

CONSTRUCTION SIGN DETAILS  
WARNING SIGNS


| WORD    | LETTER SPACING |
|---------|----------------|
| AHEAD   | Standard       |
| 200 FT  | Standard       |
| 350 FT  | Standard       |
| 500 FT  | Standard       |
| 1000 FT | Reduce 40%     |
| 1500 FT | Reduce 40%     |
| ½ MILE  | Reduce 50%     |
| 1 MILE  | Standard       |

\* DISTANCE MESSAGES




W16-7aP-18

Legend: black (non-refl)  
Background: orange




W21-50-48

Legend: black (non-refl)  
Background: orange




W21-53-48

Legend: black (non-refl)  
Background: orange




W20-51-48

Legend: black (non-refl)  
Background: orange




W21-51-48

Legend: black (non-refl)  
Background: orange




W22-8-48

Legend: black (non-refl)  
Background: orange




W16-7aP-18



W20-52P-54

Legend: black (non-refl)  
Background: orange




W21-52-48

Legend: black (non-refl)  
Background: orange


|  |                                       |  |
|--|---------------------------------------|--|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                       | This document was originally<br>issued and sealed by<br><br>Kirk J Hoff,<br><br>Registration Number<br>PE- 4683,<br><br>on 11/1/19 and the original<br>document is stored at the<br>North Dakota Department<br>of Transportation |
| 5-31-18                                      |                                       |  |
| REVISIONS                                    |                                       |  |
| DATE   | CHANGE                                |  |
| 11-01-19                                     | Added details for sign<br>W16-7aP-18. |  |

BARRICADE AND CHANNELIZING DEVICE DETAILS




Provide horizontal, circumferential, alternating orange and white retroreflective stripes 4" to 6" wide for drum markings. Use a minimum of two orange and two white stripes with the top stripe being orange for each drum. Do not exceed 3" nonretroreflectORIZED spaces between the horizontal orange and white stripes. Avoid placement of stripes on drum ribs or indentations. Use closed top drums that will not allow collection of debris. Do not place ballast on the top of drum.


Provide alternating orange and white retroreflective stripes, sloping downward in direction vehicular traffic is to pass. Place retroreflective sheeting on both sides of panel with a minimum of 270 square inches of retroreflective area facing vehicular traffic. Where the height of the retroreflective material on the vertical panel is 36 inches or more, use a stripe width of 6 inches.




Provide retroreflectORIZATION of cones more than 36" in height by alternating orange and white retroreflective stripes. Use a minimum of two orange and two white stripes for each cone with the top stripe being orange. Use maximum 3" nonretroreflectORIZED space between the orange and white stripes.



Provide retroreflectORIZATION of tubular markers more than 42" in height by alternating four 4" to 6" wide orange and white stripes with the top stripe being orange.




- INSTALLATION NOTES:
1. Drill installation holes to diameter and depth required by manufacturer's specifications.
  2. For removal, remove anchors and fill installation hole with an epoxy designed to bond to pavement surface.
  3. In lieu of bolted down base, use an 8" x 8" butyl pad or hot melt butyl. Remove butyl as close as possible to pavement surface.



BARRICADE BLADE DETAIL


BARRICADE ASSEMBLY DETAIL (Aluminum Barricade Rails)

NOTE: For barricade markings use alternating orange and white retroreflective stripes, sloping downward in the direction traffic is to pass. Place retroreflective sheeting on both sides of the rails with a minimum of 270 square inches of visible retroreflective area facing vehicular traffic. When the barricade length is less than 36", use a rail stripe width of 4".




TYPE I BARRICADE


TYPE II BARRICADE  
BARRICADE RAIL DETAILS



SIDE VIEW




TYPE III BARRICADE



ELEVATION VIEW

BARRICADE ASSEMBLY DETAIL (Wood or Plastic Rails)

SIDE VIEW



REFLECTOR DETAIL

ELEVATION

DELINEATORS

MINIMUM BALLAST (For each side of barricade support)

|              |                    |
|--------------|--------------------|
| Without Sign | 4 - 25 lb sandbags |
| With Sign    | 6 - 25 lb sandbags |


Note: Number of sandbags based on a wind speed of 55 MPH. Sandbags assumed to be placed at or near the ends of the skids.

|  |  |
|--|--|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |  |
| 10-3-13                                      |  |
| REVISIONS                                    |  |
| DATE   | CHANGE   |
| 9-27-17<br>11-01-19                          | Updated to active voice<br>Revised details for Flexible Delineator |


This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 11/1/19 and the original document is stored at the North Dakota Department of Transportation

CONSTRUCTION SIGN PUNCHING AND MOUNTING DETAILS


Note: In curb sections, place signs a minimum horizontal distance of 2' from face of the curb to near edge of the sign.




TYPICAL SECTION  
(48" x 48" diamond warning sign shown)




24" x 24"  
ROUTE MARKER  
ASSEMBLY




36" x 36"  
ROUTE MARKER  
ASSEMBLY




18" x 18"  
DIAMOND SIGN




108" x 48" SIGN




48" x 48" DIAMOND SIGN  
(with 30" x 30" secondary sign)




48" x 48" DIAMOND SIGN  
(with 30" x 24" secondary sign)




R1-2-60 - YIELD SIGN




W14-3-64 - PENNANT SIGN




R1-1-48 - STOP SIGN  
(with R6-1-54 sign as required)




R1-1-48 - STOP SIGN  
(with R1-50P-24 sign as required)




48" x 48" SIGN  
(with R6-1-54 sign as required)




48" x 48" SIGN  
(with R2-1aP-24 sign as required)




24" x 36" SIGN




30" x 24" SIGN




72" x 36" SIGN




72" x 24" SIGN




60" x 24" SIGN



48" x 24" SIGN



PORTABLE SIGN SUPPORT  
LOW-MOUNTING HEIGHT



PORTABLE SIGN SUPPORT  
HIGH-MOUNTING HEIGHT

NOTES:

1. Sign Supports: Galvanize or paint supports. Minimum post sizes are 2.5 lb/ft u-channel or 2" x 2" x 12 gauge steel perforated tube, except where noted. When installing signs on u-channel, minimum post size for assemblies containing a secondary sign is 3.0 lb/ft. Post sizes based on a wind speed of 55 MPH.  
  
Place signs over 50 square feet on 2½" x 2½" perforated tube supports as a minimum.  
  
Do not attach guy wires to sign supports. Attach wind beams behind sign panels when used with u-posts.
2. Sign Panels: Provide sign panels made of 0.100" aluminum, ½" plywood, or other approved material, except where noted. Punch all holes round for ⅝" bolts.
3. Alternate Messages: Install and remove alternate message signs on reflectorized plate (without borders) as required. (i.e. "Left" and "Right" message on lane closure sign)
4. Route Marker Auxiliary Signs: Provide route marker auxiliary signs, such as the cardinal direction and directional arrows, with a background and legend that match the route marker they are used with:

Interstate - white legend on blue background  
Interstate Business Loop - white legend on green background  
US and State - black legend on white background  
County - yellow legend on blue background

5. Vertical Clearance: Install signs with a vertical clearance of 5'-0" (see TYPICAL SECTION.). In areas where parking or pedestrian movements are likely or the view of the sign may be obstructed, install signs with a vertical clearance of 7'-0" from the top of the curb or from the near edge of the driving lane in absence of a curb.

The vertical clearance to secondary signs is 1'-0" less than the vertical clearance stated above.

Provide a minimum clearance of 7'-0" from the ground at the post for signs with an area exceeding 50 square feet.

6. Portable Signs: Provide portable signs that meet the vertical clearance stated above when it is necessary to place signs within the pavement surface.

Use of low-mounting height (minimum 12" vertical clearance) portable signs for 5 days or less, is allowed as long as the view of the sign is not obstructed. Time delays caused by unforeseen circumstances, such as equipment breakdown, rain, subgrade failures, etc., will not accrue towards the 5 day period. Use of R9-8 through R9-11a series, W1-6 through W1-8 series, M4-10, and E5-1 is allowed for longer than 5 days.

Restrict signs mounted on portable sign supports shown in the LOW-MOUNTING HEIGHT and HIGH-MOUNTING HEIGHT details to a maximum surface area of 16 square feet.

MINIMUM BALLAST  
(For each side of sign support base)

| Sign Panel Mounting Height (ft) | Number of 25 lb sandbags for 4' x 4' sign panel |
|---------------------------------|---|
| 1'                              | 6   |
| 5'                              | 8   |
| 7'                              | 10  |





Note: The number of sandbags are based on a wind speed of 55 MPH. Place sandbags at or near the ends of skids.

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                             |
|--|-----------------------------|
| 10-4-13                                      |                             |
| REVISIONS                                    |                             |
| DATE   | CHANGE                      |
| 11-14-13                                     | Revised Note 6              |
| 9-27-17                                      | Updated to active voice     |
| 11-01-19                                     | Revised 60"x24" sign detail |




This document was originally issued and sealed by  
  
Kirk J Hoff,  
Registration Number  
PE-4683,  
on 11/1/19 and the original document is stored at the North Dakota Department of Transportation



SHOULDER CLOSURES AND BRIDGE PAINTING LAYOUTS



- Notes
- Variables
    - S = Numerical value of speed limit or 85th percentile.
    - W = The width of the taper in feet.
    - L = Minimum length of taper,  $S \times W$  for freeways, expressways, and all other roads with speeds of 45 mph or greater, or  $W \times S^2 / 60$  for urban, residential, and other streets with speeds of 40 mph or less.
  - Space delineator drums for tapering traffic at dimension "S". Space delineator drums or tubular markers for tangents at 2 times "S".
  - Sequencing Arrow Panels
    - Use Type A on roadways with slow moving traffic speeds and low volume (25 mph or less and 750 ADT or less).
    - Use Type B on roadways with moderate traffic speeds and volumes (40 mph or less and 5000 ADT or less).
    - Use Type C on roadways with high traffic speeds and volumes (over 40 mph or over 5000 ADT).
  - Re-establish speed limit. Determine exact speed limit in the field, dependent on location and conditions.
  - Determine the reduced speed limit based on the in-place speed limit before construction. Where speed reductions exceed 30 MPH, install a second speed limit sign with the desired speed reduction (not to exceed 30 mph.) Place the second speed limit sign at 1/2 B.
  - Install flags on warning signs in urban areas when signs are not portable. Mount 24 inch square flags perpendicular to the edges of the sign, and at such a distance above the edge that the flag does not touch the sign when limp.
  - Cover existing speed limit signs within a reduced speed zone.
  - As an option, use portable sign supports in lieu of post mounted signs in accordance with NDDOT Standard Drawing D-704-14.
  - Recommend 40 mph speed limit in vicinity of workers, unless location and conditions dictate otherwise.



| ADVANCE WARNING SIGN SPACING                          |                        |      |      |  |
|---|------------------------|------|------|--|
| Road Type   | Distance Between Signs |      |      |  |
|   | A                      | B    | C    |  |
| Urban - Low Speed (30 mph or less)                    | 150                    | 150  | 150  |  |
| Urban - Low Speed (over 30 to 40 mph)                 | 280                    | 280  | 280  |  |
| Urban - High Speed (over 40 mph to 50 mph)            | 360                    | 360  | 360  |  |
| Rural - High Speed (over 50 mph to 65 mph)            | 720                    | 720  | 720  |  |
| Urban Expressway and Freeway (55 mph to 60 mph)       | 850                    | 1350 | 2200 |  |
| Rural Expressway and Freeway (70 mph to 75 mph)       | 1000                   | 1500 | 2640 |  |
| Interstate/4-Lane Divided (Maintenance and Surveying) | 750                    | 1000 | 1500 |  |



| Longitudinal Buffer Space |                   |
|---------------------------|-------------------|
| Speed (mph)               | Length Min (feet) |
| 20                        | 115               |
| 25                        | 155               |
| 30                        | 200               |
| 35                        | 250               |
| 40                        | 305               |
| 45                        | 360               |
| 50                        | 425               |
| 55                        | 495               |
| 60                        | 570               |
| 65                        | 645               |
| 70                        | 730               |
| 75                        | 820               |

| NORTH DAKOTA DEPARTMENT OF TRANSPORTATION |  |
|---|--|
| 9-27-13                                   |  |
| REVISIONS                                 |  |
| DATE                                      | CHANGE   |
| 8-17-17<br>11-01-19                       | Updated notes & revised signs<br>Revised drum spacing & signs nos. |


This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 11/1/19 and the original document is stored at the  
North Dakota Department  
of Transportation

MOBILE OPERATION  
(PAVEMENT MARKING)


D-704-27




Two-Way Roadway with Paved Shoulders




Two-Way Roadway without Paved Shoulders



Undivided Multi-Lane Roadway




A = Left Right Center



Divided Multi-Lane Highway

Sign Details



- Notes
1. Use additional vehicles you choose to be in the convoy with truck mounted attenuators, at your own expense.
  2. Display yellow rotating beacons or strobe lights on shadow and work vehicles, unless otherwise stated in the plans.
  3. Use Type B or Type C flashing arrow panels controlled from inside the vehicle.
  4. Provide each vehicle with two-way electronic communication capability.
  5. Move shadow vehicle 1 first to shadow other convoy vehicles when convoy changes lane.
  6. Vary vehicle spacing between shadow vehicle 1 and shadow vehicle 2 based on sight distance restrictions. Motorists approaching the work convoy need to see trail vehicle in time to slow down and/or change lanes as they approach shadow vehicle.
  7. Sign Colors  
Letters = Black  
Border = Black  
Background = Orange
  8. As an option, use shadow vehicle 2 the paint tender vehicle.
  9. Use sign CW21-10A only during painting operation.
  10. Pull over work and shadow vehicles periodically to allow motor vehicle traffic to pass on two lane - two way roadways.

| KEY |                          |
|-----|--------------------------|
|     | Sign                     |
|     | Truck mounted attenuator |
|     | Flashing arrow panels:   |
|     | Right directional        |
|     | Left directional         |
|     | Double arrow directional |
|     | Caution Mode             |

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
|--|---|
| 9-27-13                                      |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 6-18-14                                      | Removed shadow vehicle 2 on two lane roadways |
| 9-27-17                                      | Updated to active voice                       |
| 11-08-19                                     | Changed Standard Heading                      |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 11/08/19 and the original document is stored at the  
North Dakota Department  
of Transportation

Work area





Flagger

Sign

KEY


S = Numerical value of speed limit or 85th percentile.

| Road Type                                  | Distance Between Signs Min. (ft) |     |     |
|--|----------------------------------|-----|-----|
|  | A                                | B   | C   |
| Urban - High Speed (over 45 mph to 50 mph) | 360                              | 360 | 360 |
| Rural - High Speed (over 50 mph to 65 mph) | 720                              | 720 | 720 |



PORTABLE RUMBLE STRIPS ARRAY  
TYPES OF MOVEMENT AND MAXIMUM ALLOWANCES

- Notes:
- Determine speed in the field based on location and conditions.
  - Re-establish the speed limit. Determine the exact speed limit in the field, dependent on location and conditions.
  - Sign R2-1aP-24 is not required when pilot car operation is used.
  - Do not use rumble strips on a non paved surface or in a pre-construction speed zone of 45 mph or less.



PORTABLE RUMBLE STRIPS ARRAY DETAIL

PORTABLE RUMBLE STRIPS  
AT TEMPORARY ROAD CLOSURE

NORTH DAKOTA  
DEPARTMENT OF TRANSPORTATION

02-22-22

REVISIONS

DATE03/07/23


CHANGEUse changed to min 45 mph.

KIRK J. HOFF  
REGISTERED  
PROFESSIONAL  
PE-4683  
ENGINEER  
NORTH DAKOTA

03/07/23

PORTABLE SIGN SUPPORT ASSEMBLY

D-704-50





- Notes:
- 1. Maximum 250 pound weight of assembly.
  - 2. Use a 14" wheel and tire.
  - 3. Use no automotive and equipment axle assemblies for trailer-mounted sign supports.
  - 4. Other NCHRP 350 or MASH crash tested assemblies are acceptable.

|  |                               |
|--|-------------------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                               |
| 11-23-10                                     |                               |
| REVISIONS                                    |                               |
| DATE   | CHANGE                        |
| 12/02/2020                                   | Updated Note to active voice. |




PIPE SUPPORT AND SIGN MOUNTING DETAILS


D-754-7




Flat Sheet Sign Clamp Mounting Details




Panel Sign Clamp Mounting Details




Clamp Detail




Steel Channel Detail




Alternate A  
12" Extruded Panel



Alternate B  
12" Extruded Panel



Slotted Hole Detail




6" Extruded Panel

Aluminum Panel Details


(A) Punch slotted holes in aluminum panels at 1'-0" on center, space from end as listed below:

|                            |            |
|----------------------------|------------|
| 12" even length panels     | 4'-0" etc. |
| 9" odd + 6" length panels  | 5'-6" etc. |
| 6" odd length panels       | 5'-0" etc. |
| 3" even + 6" length panels | 4'-6" etc. |


Wall thickness = .078" unless specified otherwise.  
All inside and outside corners = .031" radius unless specified otherwise.



Flat Washer Detail



Side View



Top View

Post Cap Detail

Furnish post caps for all steel or aluminum posts or weld a 1/8" plate all around.

| Post Size dia | Clamp Gauge min |
|---------------|-----------------|
| 3 1/2" to 5"  | 11              |
| 6" to 12"     | 10              |

| Post Size dia (in) | D (in)  |
|--------------------|---------|
| 3 1/2              | 3       |
| 4                  | 3 3/16  |
| 5                  | 5 1/8   |
| 6                  | 7 1/16  |
| 8                  | 13 1/16 |
| 10                 | 20 3/4  |
| 12                 | 29 5/8  |


| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |  |
|--|--|
| 2-21-14                                      |  |
| REVISIONS                                    |  |
| DATE   | CHANGE   |
| 08-30-18                                     | Updated to active voice, defined bolt & washer for fastening sign. |
| 08-29-19                                     | New Design Engineer PE Stamp.                                      |
| 10-19-22                                     | Added washers to clamp.  |



10/20/22

LETTER AND ARROW DETAILS


D-754-9




DETERMINE SIZE OF THE FRACTION AS FOLLOWS:

| SYMBOL | TITLE                   | RATIO TO HEIGHT OF CAPITAL OR UPPER CASE |
|--------|-------------------------|--|
| A      | Letter height           | 1.0 of capital or upper case             |
| B      | Fraction height         | 1.5 X A                                  |
| C      | Fraction width          | 2.5 X A                                  |
| D      | Fraction width          | 2 X A                                    |
| E      | Space to next character | 1 to 1.5 X A                             |
| F(A)   | Length of diagonal      | 1.75 X A                                 |


(A) Center diagonal stroke of fraction optically.



TYPE A



TYPE B




TYPE D


| DESIGNATION | LETTER SIZE (Upper Case) | A       | B       | C      | D      | E      | F   | G     |
|-------------|--------------------------|---------|---------|--------|--------|--------|-----|-------|
| ND_6IN      | 6"                       | 12"     | 9.125"  | 3"     | 1"     | 0.625" | 20" | 13.5" |
| ND_8IN      | 8"                       | 15.125" | 11.563" | 3.75"  | 1.313" | 0.813" | 25" | 17"   |
| ND_10IN     | 10"                      | 18.25"  | 14"     | 4.5"   | 1.5"   | 0.75"  | 30" | 20"   |
| ND_12IN     | 12"                      |         |         |        |        |        |     |       |
| ND_13IN     | 13.3"                    |         |         |        |        |        |     |       |
| ND_16IN     | 16"                      | 22.25"  | 17"     | 5.375" | 1.75"  | 1"     | 35" | 25"   |
| ND_20IN     | 20"                      |         |         |        |        |        |     |       |

NOTE: Arrow size on gore signs is based on the letter size of "EXIT".


| DESIGNATION | LETTER SIZE (Upper Case) | A   | B      | C     | D      | E      | F   |
|-------------|--------------------------|-----|--------|-------|--------|--------|-----|
| ND_2IN      | 2"                       | 2"  | 1.625" | 0.75" | 0.125" | 0.125" | 3"  |
| ND_4IN      | 4"                       | 4"  | 3.313" | 1.5"  | 0.25"  | 0.25"  | 6"  |
| ND_6IN      | 6"                       | 6"  | 4.875" | 2.25" | 0.375" | 0.375" | 9"  |
| ND_8IN      | 8"                       | 8"  | 6.625" | 3"    | 0.5"   | 0.5"   | 12" |
| ND_10IN     | 10"                      | 10" | 8.375" | 3.75" | 0.75"  | 0.75"  | 15" |
| ND_12IN     | 12"                      | 12" | 10"    | 4.5"  | 0.875" | 0.875" | 18" |



TYPICAL SPACING




ROUNDBOUT



SPECIAL

| DESIGNATION | A  | B      | C      | D      | E      | F     | USES                       |
|-------------|----|--------|--------|--------|--------|-------|----------------------------|
| ND_0.75IN   | 2" | 1.625" | 0.75"  | 0.125" | 0.125" | 7.75" | Parking Signs (Regulatory) |
| ND_2.625IN  | 7" | 5.75"  | 2.625" | 0.5"   | 0.5"   | 15"   | Frontage Road Signs        |



DOWN ARROW

| DESIGNATION | LETTER SIZE (Upper Case) | A     | B      | C      | D      | E      | F      | G       | H      | J       | K      | L      | M      |
|-------------|--------------------------|-------|--------|--------|--------|--------|--------|---------|--------|---------|--------|--------|--------|
| ND_6IN      | 6"                       | 5.25" | 4.688" | 2"     | 0.375" | 0.375" | 6.5"   | 10.125" | 6.094" | 10.75"  | 1.168" | 1.25"  | 2.625" |
| ND_8IN      | 8"                       | 7"    | 5.75"  | 2.625" | 0.5"   | 0.5"   | 8.688" | 13.5"   | 8.166" | 14.333" | 1.557" | 1.667" | 3.5"   |


| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |  |
|--|--|
| 8-3-11                                       |  |
| REVISIONS                                    |  |
| DATE   | CHANGE   |
| 7-8-14                                       | Revised gore sign and added 4" D & D arrow                 |
| 5-4-16                                       | Revised Distance & Destination and Typical Spacing details |
| 4-23-18                                      | Revised arrow details                                      |
| 8-30-18                                      | Updated notes to active voice.                             |
| 8-29-19                                      | New Design Engr PE Stamp.                                  |
| 8-05-24                                      | Electronic Stamp/Signature.                                |



08/05/24


Notes:

1. Curbed Roadways: Use a 3' clearance from face of the curb except where right of way or sidewalk width is limited; Use a minimum 2' clearance. Increase the horizontal clearance if required to maintain a minimum sidewalk clear width of 4' from the sign support, not including any attached curb.
2. Minimum vertical clearance: Provide at least 5' measured from the bottom of the sign to the edge of the driving lane or auxiliary lane at the side of the road in rural districts. Provide at least 7' clearance to the bottom of the sign, where parking or pedestrian movements occur.
- Install signs on expressways a minimum height of 7'.
- Install adopt-a-highway signs on Freeways at least 7' above the edge of the driving lane.
- Maximum vertical clearance is 6" greater than the minimum vertical clearance.
3. Offset signs: Use a vertical clearance of 5' above the edge of the driving lane for signs placed 30 feet or more from the edge of the traveled way.
4. Provide a horizontal clearance from edge of shared use path to edge of sign of 3', except where width is limited. Provide a minimum clearance of 2'.




Typical Section (without curb)

| Horizontal Clearance Table |           |
|----------------------------|-----------|
| Shoulder Width ft          | Offset ft |
| 0 to 2                     | 16        |
| >2 to 4                    | 18        |
| >4 to 6                    | 20        |
| >6 to 8                    | 22        |
| >8 to 10                   | 24        |




Typical Section (with curb)  
Residential or Business District



Stop Sign Location  
Wide Throat Intersection  
Use layout for the placement of "Stop" signs.

| Radius ft. | Y-max. ft. | Y-min. ft. |
|------------|------------|------------|
| 40         | 50         | 15         |
| 45         | 50         | 18         |
| 50         | 50         | 21         |
| 55         | 50         | 25         |
| 60         | 50         | 28         |
| 65         | 50         | 32         |
| 70         | 50         | 35         |
| 75         | 50         | 39         |
| 80         | 50         | 43         |



Shared Use Path  
Bicycle - Pedestrian Path



| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                |
|--|--------------------------------|
| 10-3-13                                      |                                |
| REVISIONS                                    |                                |
| DATE   | CHANGE                         |
| 7-8-14                                       | Revised note 2, added note 4.  |
| 8-30-18                                      | Updated notes to active voice. |
| 8-29-19                                      | New Design Engineer PE Stamp.  |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 8/29/19 and the original document is stored at the North Dakota Department of Transportation



| Telescoping Perforated Tube |               |                       |                 |                       |           |                                   |                              |
|-----------------------------|---------------|-----------------------|-----------------|-----------------------|-----------|-----------------------------------|------------------------------|
| Number of Posts             | Post Size In. | Wall Thick-ness Gauge | Sleeve Size In. | Wall Thick-ness Gauge | Slip Base | Anchor Size Without Slip Base In. | Anchor Wall Thick-ness Gauge |
| 1                           | 2             | 12                    |                 |                       | No        | 2½                                | 12                           |
| 1                           | 2¼            | 12                    |                 |                       | No        | 2½                                | 12                           |
| 1                           | 2½            | 12                    |                 |                       | (B)       | 3(C)                              | 7                            |
| 1                           | 2½            | 10                    |                 |                       | Yes       |                                   | 7                            |
| 1                           | 2¼            | 12                    | 2½(D)           | 12                    | Yes       |                                   | 7                            |
| 1                           | 2½            | 12                    | 2¼              | 12                    | Yes       |                                   | 7                            |
| 2                           | 2½            | 10                    |                 |                       | Yes       |                                   | 7                            |
| 2                           | 2¼            | 12                    | 2½(D)           | 12                    | Yes       |                                   | 7                            |
| 2                           | 2½            | 12                    | 2¼              | 12                    | Yes       |                                   | 7                            |
| 3 & 4                       | 2½            | 12                    |                 |                       | Yes       |                                   | 7                            |
| 3 & 4                       | 2½            | 10                    |                 |                       | Yes       |                                   | 7                            |
| 3 & 4                       | 2½            | 12                    | 2¼              | 12                    | Yes       |                                   | 7                            |
| 3 & 4                       | 2¼            | 12                    | 2½(D)           | 12                    | Yes       |                                   | 7                            |
| 3 & 4                       | 2½            | 10                    | 2¾              | 10                    | Yes       |                                   | 7                            |


(B) - Provide a shim as specified by the manufacturer when placing 2½", 12 gauge posts in standard soils without breakaway bases. Provide breakaway base when placing the support in weak soils. The Engineer will determine if the soils are weak. Weak soils are classified as boggy, wet, or loose soil areas.  
(C) - 3" anchor unit  
(D) - 2½" x 12 ga. x 18" minimum length external sleeve required.



MULTI-DIRECTIONAL SLIP BASE ASSEMBLY:  
Inserting 2½" x 12 ga with 2¼" x 12 ga and inserting 2½" 10 ga with 2¾" x 10 ga to achieve higher load ability is allowed.


#### SHOULDER BOLT

Shimming agent to reduce tolerance between 3" anchor unit and 2½" post.  
(use standard ¾" diameter grade 8 bolt with proper shim)




3" ANCHOR UNIT

#### Mounting Details Perforated Tube




SLIP BASE FOR 2½" POST



POST LOCKING WEDGE

Ductile Iron Casting class 65-45-12.  
Hot Dip Galvanize ASTM A153




SLIP BASE DETAIL

| Properties of Telescoping Perforated Tubes |                    |                     |                      |                                    |                                   |                                  |  |
|--|--------------------|---------------------|----------------------|------------------------------------|-----------------------------------|----------------------------------|--|
| Tube Size In.                              | Wall Thickness In. | U.S. Standard Gauge | Weight Per Foot Lbs. | Moment of Inertia In. <sup>4</sup> | Cross Sect. Area In. <sup>2</sup> | Section Modulus In. <sup>3</sup> |  |
| 1½ x 1½                                    | 0.105              | 12                  | 1.702                | 0.129                              | 0.380                             | 0.172                            |  |
| 2 x 2                                      | 0.105              | 12                  | 2.416                | 0.372                              | 0.590                             | 0.372                            |  |
| 2¼ x 2¼                                    | 0.105              | 12                  | 2.773                | 0.561                              | 0.695                             | 0.499                            |  |
| 2¾ x 2¾                                    | 0.135              | 10                  | 3.432                | 0.605                              | 0.841                             | 0.590                            |  |
| 2½ x 2½                                    | 0.105              | 12                  | 3.141                | 0.804                              | 0.803                             | 0.643                            |  |
| 2½ x 2½                                    | 0.135              | 10                  | 4.006                | 0.979                              | 1.010                             | 0.783                            |  |

The 2 ¾" size 10 gauge is shown as 2.19" size on the plans;  
The 2 ½" size is shown as 2.51" size on the plans.

NOTE:

- 4" Vertical clearance of anchor or breakaway base. The 4" x 60" measurement is above and below post location and also back and ahead of post.
- Provide 7 gauge HRPO commercial quality ASTM A569 and 3" x 3" x 7" gauge ASTM A500 grade B anchor material with 43.9 KSI yield strength and 59.3 KSI tensile strength. Hot dip galvanize anchor per ASTM A123/153. Tolerances on anchor unit and slip base bottom assembly are +/- 0.005" unless otherwise noted.
- Eliminate wings when anchor is used in concrete sidewalk.
- Provide a minimum 8" distance between the first and fourth post on four post signs.
- Install in accordance with manufacturers recommendation.
- Use a minimum ½" diameter x 4" grade 8 concrete fastener for surface mount breakaway base.



SURFACE MOUNT ANCHOR BASE

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
|--|---|
| 8-6-09                                       |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 8-30-18                                      | Updated notes to active voice & corrected max height of base. |
| 8-29-19                                      | New Design Engineer PE Stamp.                                 |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683  
on 8/29/19 and the original document is stored at the North Dakota Department of Transportation

Breakaway Coupler System  
for Perforated Tubes



Notes:

1. 4" Vertical clearance of anchor or breakaway base. The 4" x 60" measurement is above and below post location and also back and ahead of post.
2. Use anchor unit of the same size and specification as the post.
3. Provide a minimum 8' distance between the first and fourth post on four post signs.
4. Use the breakaway base system on standard D-754-24 or the breakaway coupling system manufactured from material meeting the requirements of ASTM A325 fasteners with the special requirements specified by DENT BREAKAWAY IND., INC. which meets the test requirements of NCHRP Report 350.



| Number of Posts | Telescoping Perforated Tube |                       |                 |                       |           |                                   |                             |
|-----------------|-----------------------------|-----------------------|-----------------|-----------------------|-----------|-----------------------------------|-----------------------------|
|                 | Post Size In.               | Wall Thick-ness Gauge | Sleeve Size In. | Wall Thick-ness Gauge | Slip Base | Anchor Size Without Slip Base In. | Anchor Wall Thickness Guage |
| 1               | 2                           | 12                    |                 |                       | No        | 2¼                                | 12                          |
| 1               | 2¼                          | 12                    |                 |                       | No        | 2½                                | 12                          |
| 1               | 2½                          | 12                    |                 |                       | (B)       | 3(C)                              | 7                           |
| 1               | 2½                          | 10                    |                 |                       | Yes       |                                   | 7                           |
| 1               | 2¼                          | 12                    | 2               | 12                    | Yes       |                                   | 7                           |
| 1               | 2½                          | 12                    | 2¼              | 12                    | Yes       |                                   | 7                           |
| 2               | 2½                          | 10                    |                 |                       | Yes       |                                   | 7                           |
| 2               | 2¼                          | 12                    | 2               | 12                    | Yes       |                                   | 7                           |
| 2               | 2½                          | 12                    | 2¼              | 12                    | Yes       |                                   | 7                           |
| 3 & 4           | 2½                          | 12                    |                 |                       | Yes       |                                   | 7                           |
| 3 & 4           | 2½                          | 10                    |                 |                       | Yes       |                                   | 7                           |
| 3 & 4           | 2½                          | 12                    | 2¼              | 12                    | Yes       |                                   | 7                           |
| 3 & 4           | 2¼                          | 12                    | 2               | 12                    | Yes       |                                   | 7                           |
| 3 & 4           | 2½                          | 10                    | 2¾              | 10                    | Yes       |                                   | 7                           |

(B) - 2½" 12 gauge posts do not need breakaway bases unless support is placed in boggy, wet, or loose soil areas.

(C) - 3" anchor unit




Max protection of the stub post is 4" above a 60" chord aligned radially to the center line of the highway and connecting any point, within the length of the chord, on the ground surface on one side of the support to a point in the ground surface on the other side.




|  |   |  |
|--|---|--|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   | This document was originally<br>issued and sealed by<br><br>Kirk J Hoff,<br><br>Registration Number<br>PE- 4683,<br><br>on 8/30/19 and the original<br>document is stored at the<br>North Dakota Department<br>of Transportation |
| 10-3-2013                                    |   |  |
| REVISIONS                                    |   |  |
| DATE   | CHANGE  |  |
| 8-30-18<br>8-30-19                           | Updated notes to active voice.<br>New Design Engr PE Stamp. |  |

Mounting Details Perforated Tube




Side View




Top View

STRINGER MOUNTING  
(WITH STRINGER IN FRONT OF POST)




Side View




Top View


STRAP DETAIL




STREET NAME SIGNS AND ONE WAY SIGNS  
SINGLE POST ASSEMBLY  
ONE STRINGER OR BACK TO BACK MOUNTING



ANCHOR UNIT AND POST ASSEMBLY




BOLT MOUNTING



Top View

BACK TO BACK MOUNTING



| Properties of Telescoping Perforated Tubes |                    |                     |                      |                                    |                                   |                                  |
|--|--------------------|---------------------|----------------------|------------------------------------|-----------------------------------|----------------------------------|
| Tube Size In.                              | Wall Thickness In. | U.S. Standard Gauge | Weight Per Foot Lbs. | Moment of Inertia In. <sup>4</sup> | Cross Sect. area In. <sup>2</sup> | Section Modulus In. <sup>3</sup> |
| 1 1/2 x 1 1/2                              | 0.105              | 12                  | 1.702                | 0.129                              | 0.380                             | 0.172                            |
| 2 x 2                                      | 0.105              | 12                  | 2.416                | 0.372                              | 0.590                             | 0.372                            |
| 2 1/4 x 2 1/4                              | 0.105              | 12                  | 2.773                | 0.561                              | 0.695                             | 0.499                            |
| 2 3/16 x 2 3/16                            | 0.135              | 10                  | 3.432                | 0.605                              | 0.841                             | 0.590                            |
| 2 1/2 x 2 1/2                              | 0.105              | 12                  | 3.141                | 0.804                              | 0.803                             | 0.643                            |
| 2 1/2 x 2 1/2                              | 0.135              | 10                  | 4.006                | 0.979                              | 1.010                             | 0.783                            |

The 2 3/16" size 10 gauge is shown as 2.19" size on the plans.  
The 2 1/2" size is shown as 2.51" size on the plans.

Note:




1. Horizontal stringers - Use perforated tubes or 1 3/4" x 3/16" thick, 1.08 lbs./ft aluminum or 3.16 lbs./ft steel z bar stringers.
2. Use minimum outside diameter 1 5/16" ± 1/16" and 10 gauge thick metal washers on sign face.
3. Place No Parking signs with directional arrows at a 30 to 45 degree angle with the line of traffic flow. Turning the support to the correct angle for No Parking signs requiring the above angles is allowed. If the No Parking sign is placed with another sign that requires placement at a 90 degree angle with the line of traffic flow, use the detailed angle strap to mount the No Parking sign. Use flat washers and lock washers with all nylon washers.
4. Punching the sign backing and placing the bolt through the sign, the stringer and the post is allowed in lieu of using the bent bolt to attach the post to the stringer.
5. 4" vertical clearance of anchor or breakaway base. The 4" x 60" measurement is above and below post location and also back and ahead of post.

| Number of Posts | Telescoping Perforated Tube |                      |                 |                      |           |                                   |                             |
|-----------------|-----------------------------|----------------------|-----------------|----------------------|-----------|-----------------------------------|-----------------------------|
|                 | Post Size In.               | Wall Thickness Gauge | Sleeve Size In. | Wall Thickness Gauge | Slip Base | Anchor Size Without Slip Base In. | Anchor Wall Thickness Gauge |
| 1               | 2                           | 12                   |                 |                      | No        | 2 1/4                             | 12                          |
| 1               | 2 1/4                       | 12                   |                 |                      | No        | 2 1/2                             | 12                          |
| 1               | 2 1/2                       | 12                   |                 |                      | (B)       | 3(C)                              | 7                           |
| 1               | 2 1/2                       | 10                   |                 |                      | Yes       |                                   | 7                           |
| 1               | 2 1/4                       | 12                   | 2 1/2(D)        | 12                   | Yes       |                                   | 7                           |
| 1               | 2 1/2                       | 12                   | 2 1/4           | 12                   | Yes       |                                   | 7                           |
| 2               | 2 1/2                       | 10                   |                 |                      | Yes       |                                   | 7                           |
| 2               | 2 1/4                       | 12                   | 2 1/2(D)        | 12                   | Yes       |                                   | 7                           |
| 2               | 2 1/2                       | 12                   | 2 1/4           | 12                   | Yes       |                                   | 7                           |
| 3 & 4           | 2 1/2                       | 12                   |                 |                      | Yes       |                                   | 7                           |
| 3 & 4           | 2 1/2                       | 10                   |                 |                      | Yes       |                                   | 7                           |
| 3 & 4           | 2 1/2                       | 12                   | 2 1/4           | 12                   | Yes       |                                   | 7                           |
| 3 & 4           | 2 1/4                       | 12                   | 2 1/2(D)        | 12                   | Yes       |                                   | 7                           |
| 3 & 4           | 2 1/2                       | 10                   | 2 3/16          | 10                   | Yes       |                                   | 7                           |

(B) - When placing 2 1/2", 12 gauge posts in standard soils without breakaway bases, provide a shim as specified by the manufacturer. Provide breakaway base when placing the support in weak soils. Engineer will determine if soils are weak. Weak soils are classified as boggy, wet, or loose soil areas.  
(C) - 3" anchor unit  
(D) - 2 1/2" x 12 ga. x 18" minimum length external sleeve required.


| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |  | This document was originally<br>issued and sealed by<br><br>Kirk J Hoff,<br><br>Registration Number<br>PE- 4683 ,<br><br>on 8/30/19 and the original<br>document is stored at the<br>North Dakota Department<br>of Transportation |
|--|--|---|
| 8-6-09                                       |  |   |
| REVISIONS                                    |  |   |
| DATE   | CHANGE   |   |
| 7-8-14<br>8-30-18<br>8-30-19                 | Revised Note 3.<br>Updated notes to active voice.<br>New Design Engr PE Stamp. |   |

## SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS REGULATORY, WARNING AND GUIDE SIGNS




## Assembly No. 6



- Notes:
1. Use 0.100 inch minimum thickness sign backing material.
  2. Use  $1\frac{1}{2}$ " x  $1\frac{1}{2}$ " perforated square tube stringers.
  3. Punch holes round for  $\frac{3}{8}$ " bolt.






Assembly No. 7






## Assembly No. 8



Assembly No. 9



Assembly No. 10




Assembly No. 11


|  |                                |
|--|--------------------------------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                |
| 12-1-10                                      |                                |
| REVISIONS                                    |                                |
| DATE   | CHANGE                         |
| 8-30-18                                      | Updated notes to active voice. |
| 8-30-19                                      | New Design Engineer PE Stamp.  |

This document was originally issued and sealed by  
 Kirk J Hoff,  
 Registration Number  
 PE-4683,  
 on 8/30/19 and the original document is stored at the  
 North Dakota Department  
 of Transportation




SIGN PUNCHING, STRINGER AND SUPPORT LOCATION  
DETAILS REGULATORY, WARNING AND GUIDE SIGNS






Assembly No. 18




Assembly No. 19



Assembly No. 20



Assembly No. 21




- Notes:
1. Use 0.100 inch minimum thickness sign backing material.
  2. Use 1½" x 1½" perforated square tube stringers.
  3. Punch holes round for ⅜" bolt.

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                |
|--|--------------------------------|
| 12-1-10                                      |                                |
| REVISIONS                                    |                                |
| DATE   | CHANGE                         |
| 8-30-18                                      | Updated notes to active voice. |
| 8-30-19                                      | New Design Engineer PE Stamp.  |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 8/30/19 and the original document is stored at the  
North Dakota Department  
of Transportation


SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS  
REGULATORY, WARNING AND GUIDE SIGNS

D-754-41




ASSEMBLY NO. 64

- Notes:
1. Use 0.100 inch minimum thickness sign backing material.
  2. Use 1½"x1½" perforated square tube stringers.
  3. Punch holes round for ⅜" bolt.



ASSEMBLY NO. 65

ASSEMBLY NO. 66












ASSEMBLY NO. 67

|  |   |  |
|--|---|--|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   | This document was originally<br>issued and sealed by<br><br>Kirk J Hoff,<br><br>Registration Number<br>PE- 4683,<br><br>on 8/30/19 and the original<br>document is stored at the<br>North Dakota Department<br>of Transportation |
| 8-22-12                                      |   |  |
| REVISIONS                                    |   |  |
| DATE   | CHANGE  |  |
| 8-30-18<br>8-30-19                           | Updated notes to active voice.<br>New Design Engineer PE Stamp. |  |

SIGN PUNCHING, STRINGER AND SUPPORT LOCATION DETAILS  
FOR VARIABLE LENGTH SIGNS

D-754-49



- Notes:
1. Use 0.100 minimum thickness sign backing material.
  2. Use 1½" x 1½" perforated square tube stringers.
  3. Punch holes round for ⅜" bolt.




| 3 POSTS     |               |              |               |
|-------------|---------------|--------------|---------------|
| Sign Length | Sign Overhang | Post Spacing | Bolt Spacing  |
| 4'-0"       | 0'-6"         | 1'-6"        | 18"           |
| 4'-6"       | 0'-6"         | 1'-9"        | 21"           |
| 5'-0"       | 0'-6"         | 2'-0"        | 24"           |
| 5'-6"       | 1'-3"         | 1'-6"        | 18"           |
| 6'-0"       | 1'-0"         | 2'-0"        | 20"           |
| 6'-6"       | 1'-3"         | 2'-0"        | 22"           |
| 7'-0"       | 1'-6"         | 2'-0"        | 24"           |
| 7'-6"       | 1'-6"         | 2'-3"        | 2-20" & 2-19" |
| 8'-0"       | 1'-9"         | 2'-3"        | 21"           |
| 8'-6"       | 2'-0"         | 2'-3"        | 2-22" & 2-23" |
| 9'-0"       | 1'-6"         | 3'-0"        | 24"           |
| 9'-6"       | 1'-9"         | 3'-0"        | 4-20" & 1-22" |
| 10'-0"      | 1'-9"         | 3'-3"        | 2-21" & 3-22" |
| 10'-6"      | 1'-9"         | 3'-6"        | 4-23" & 1-22" |
| 11'-0"      | 2'-0"         | 3'-6"        | 24"           |
| 11'-6"      | 2'-3"         | 3'-6"        | 21"           |
| 12'-0"      | 2'-4"         | 3'-8"        | 22"           |
| 12'-6"      | 2'-5"         | 3'-10"       | 23"           |
| 13'-0"      | 2'-6"         | 4'-0"        | 24"           |
| 13'-6"      | 2'-9"         | 4'-0"        | 3-22" & 4-21" |
| 14'-0"      | 3'-0"         | 4'-0"        | 2-23" & 5-22" |
| 14'-6"      | 3'-3"         | 4'-0"        | 6-23" & 1-24" |
| 15'-0"      | 3'-6"         | 4'-0"        | 24"           |
| 15'-6"      | 2'-4"         | 5'-5"        | 6-22" & 2-21" |
| 16'-0"      | 2'-5"         | 5'-7"        | 4-23" & 4-22" |
| 16'-6"      | 2'-5"         | 5'-10"       | 6-23" & 2-24" |
| 17'-0"      | 2'-6"         | 6'-0"        | 24"           |
| 17'-6"      | 3'-3"         | 5'-6"        | 22"           |
| 18'-0"      | 3'-6"         | 5'-6"        | 6-23" & 3-22" |
| 18'-6"      | 3'-9"         | 5'-6"        | 6-23" & 3-24" |
| 19'-0"      | 3'-6"         | 6'-0"        | 24"           |
| 19'-6"      | 4'-3"         | 5'-6"        | 8-22" & 2-23" |
| 20'-0"      | 4'-4"         | 5'-8"        | 8-23" & 2-22" |

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                |
|--|--------------------------------|
| 9-25-12                                      |                                |
| REVISIONS                                    |                                |
| DATE   | CHANGE                         |
| 8-30-18                                      | Updated notes to active voice. |
| 9-04-19                                      | New Design Engineer PE Stamp.  |


This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 9/04/19 and the original document is stored at the  
North Dakota Department  
of Transportation






LIGHT STANDARD, SIGNAL STANDARD,  
AND SPAN WIRE MOUNTED SIGN  
ASSEMBLY DETAIL





Section B-B  
Span Wire Mounted Sign Detail




Section A-A




Sign Mounted Beyond End of Mast Arm Detail




Mast Arm Mounted Street Name Sign Detail




Signal Standard Mounted Sign Attachment Detail




Vertical Mounting  
(Use 2 clamps per sign)




Horizontal Mounting  
alternate clamp mounting  
(Use 2 clamps per sign)



Light Standard Mounted Sign Bracket Detail  
Max. 24"x30" signs (D)




Elevation




Side View


Mast Arm Mounted Regulatory Sign Detail



Detail A



Clamp Detail



Detail B  
Steel Channel

| Post Size<br>dia. | Clamp<br>Gauge<br>min. |
|-------------------|------------------------|
| 3 1/2" to 5"      | 11                     |
| 6" to 12"         | 10                     |

| Clamp                 |          |
|-----------------------|----------|
| Post Size<br>dia. in. | D<br>in. |
| 3 1/2                 | 3        |
| 4                     | 3 3/16   |
| 5                     | 5 1/8    |
| 6                     | 7 7/16   |
| 8                     | 13 1/16  |
| 10                    | 20 3/4   |
| 12                    | 29 5/8   |


| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                |
|--|--------------------------------|
| 10-3-13                                      |                                |
| REVISIONS                                    |                                |
| DATE   | CHANGE                         |
| 8-30-18                                      | Updated notes to active voice. |
| 9-05-19                                      | New Design Engineer PE Stamp.  |

This document was originally  
issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 9/05/19 and the original  
document is stored at the  
North Dakota Department  
of Transportation


- Notes:
- (A) Use 1 3/4"x3/16" thick 1.08 lb/ft aluminum alloy Z-bar. In place of Z-bar, use two 1 3/4"x1 3/4"x3/16" angles bolted together or a 1 3/4"x2"x.188" channel.
  - (B) 3/8" U-bolt, hex. nut, lock washer, and bracket (U-bolt length depends on dia. of mast arm.)
  - (C) 3/8" U-bolt, hex. nut, lock washer, and bracket (U-bolt length depends on dia. of mast arm.)
- Maximum perforated tube lengths for mounting signs beyond end of mast arm:
- 2"x2" maximum support length 9.9'
  - 2 1/4"x2 1/4" maximum support length 12.6'
  - 2 1/2"x2 1/2" maximum support length 15.7'
- (D) Use galv. steel strap and sign attachment bracket similar to the one shown in the detail. Include all costs of bracket assembly in the price bid for flat sheet signs. Punch as shown on Standard Drawings. Provide a 7' minimum vertical clearance to the bottom of signs mounted on light standards.
  - (E) Use metal washers and nylon washers with a minimum outside dia. of 1 5/16" ± 1/16" and 10 gauge thickness on sign face.

Pavement Marking Message Details


D-762-1




22 S. F.




29 S. F.




12 S. F.



16 S. F.



27 S. F.




41 S. F.


Note: Rotate merge arrow 20° from edge of roadway.

| Speed Limit      | Chevron Width | Chevron Spacing 45° to Traffic |
|------------------|---------------|--------------------------------|
| 0-25 mph         | 8"            | 5'                             |
| 30-40 mph        | 8"            | 15'                            |
| 45 mph and above | 12"           | 25'                            |


Chevron Crosshatching Table




Centerline Pavement Marking Skip Spacing Detail




4 S. F.





22 S. F.



34.5 S. F.



46 S. F.



Continental Crosswalk Detail

- NOTES:
1. Normal width line - 6 inches wide for freeways, expressways, and ramps; 6 inches for all other roadways with speed limits > 40 mph,
  2. Use 4 or 6 inch wide pavement marking for all other roadways with speed limits ≤ 40 mph.


| Advance Placement Distance for Railroad Warning Signs |                  |
|---|------------------|
| Posted or 85th Percentile Speed                       | Advance Distance |
| 20 mph  | min. 100 ft      |
| 25 mph  | min. 100 ft      |
| 30 mph  | min. 100 ft      |
| 35 mph  | min. 100 ft      |
| 40 mph  | 125 ft           |
| 45 mph  | 175 ft           |
| 50 mph  | 250 ft           |
| 55 mph  | 325 ft           |
| 60 mph  | 400 ft           |
| 65 mph  | 475 ft           |
| 70 mph  | 550 ft           |

| NORTH DAKOTA DEPARTMENT OF TRANSPORTATION |  |
|---|--|
| 12-6-11                                   |  |
| REVISIONS                                 |  |
| DATE                                      | CHANGE                                 |
| 10-17-17                                  | Updated to active voice.               |
| 06-27-19                                  | New Design Engineer PE Stamp.          |
| 01-28-2020                                | Revised min Stop Bar distance to rail. |
| 11-22-2023                                | Revised pavement marking widths.       |




PAVEMENT MARKING


D-762-4




Two Lane Two Way  
RURAL ROADWAY




Two Lane Roadway  
INTERSTATE HIGHWAY  
Concrete Section




RURAL FIVE LANE ROADWAY  
Concrete Section




Two Lane Divided  
Rural Roadway  
PRIMARY HIGHWAY  
Asphalt Section




RURAL FIVE LANE ROADWAY  
Asphalt Section




URBAN FIVE LANE SECTION  
Concrete Section




Two Lane Divided  
Rural Roadway  
PRIMARY HIGHWAY  
Concrete Section




URBAN FIVE LANE SECTION  
Asphalt Section




RURAL FOUR LANE ROADWAY  
Asphalt Section




Two Lane Roadway  
INTERSTATE HIGHWAY  
Asphalt Section




RURAL FOUR LANE ROADWAY  
Concrete Section



URBAN FOUR LANE SECTION  
Asphalt Section



URBAN FOUR LANE SECTION  
Concrete Section



CENTERLINE PAVEMENT MARKING SKIP SPACING DETAIL

NOTES:

1. Continue edge lines through private drives and field drives. Break edge lines for intersections.

For section lines, county roads, and street approaches, stripe the radii and edge lines of the paved surface within the right of way except where curb and gutter is present.

2. Normal width line - 6 inches wide for freeways, expressways, and ramps; 6 inches for all other roadways with speed limits > 40 mph.
3. Use 4 or 6 inch wide pavement marking for all other roadways with speed limits < 40 mph.

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |                                  |
|--|----------------------------------|
| 12-1-10                                      |                                  |
| REVISIONS                                    |                                  |
| DATE   | CHANGE                           |
| 10-17-17                                     | Updated to active voice.         |
| 08-27-19                                     | New Design Engineer PE Stamp.    |
| 11-22-23                                     | Revised pavement marking widths. |
| 07-09-24                                     | Modified Note 1.                 |



CONCRETE FOUNDATIONS  
(TRAFFIC SIGNALS & HIGHWAY LIGHTING)

NOTES:

**LIGHT & SIGNAL STANDARD FOUNDATIONS:**  
See plans for conduit size, number of bends and correct position for each foundation. When conduit does not continue beyond the foundation, conduit with a 105° bend and bushings on both ends may be substituted for the 90° bends shown. See plans for correct size & location of foundations. The grade and exact location shall be established by the Engineer in the field. All reinforcing shall be Grade 60. Tie bars shall have a minimum of a 12" lap. Reinforcing may be omitted for Type I, II, V, VI & VII signal standard foundations if the anchor bolts extend to within 3" to 6" above the bottom of the foundation. A minimum of 6 anchor bolts shall be used for cantilevered structures.

**CONTROLLER CABINET FOUNDATION PAD MOUNT**  
FOUNDATION: See plans for the number of 90° bends per foundation and correct positioning. The foundation for Pad Mounted Controller Cabinet shall be of sufficient size so that there is a minimum of 3" of clearance from the outside edge of cabinet to the outside edge of the foundation on any side. The contractor shall ensure a water-tight seal between the controller cabinet and the foundation by caulking, except for V-groove.

**WORKING AREA SLAB:** The materials and preparation of this slab shall be as approved by the Engineer in the field.


**TRANSFORMER & FEED POINT CABINET FOUNDATION PAD MOUNTED:** The foundation shall have a wood float finish. All conduits shown shall be installed. Conduit that is not used at this time shall be plugged with an expandable plug.

**FEED POINT CABINET FOUNDATION PAD MOUNTED:** The foundation shall have a wood float finish. All conduits shown shall be installed. Conduit that is not used at this time shall be plugged with an expandable plug.

| LIGHT & SIGNAL FOUNDATION TABLE |                          |
|---------------------------------|--------------------------|
| FOOTING DEPTH (ft)              | LONGITUDINAL REINFORCING |
| ≤ 12                            | 8 - #5                   |
| 13 - 14                         | 8 - #6                   |
| 15 - 16                         | 8 - #7                   |
| 17 - 19                         | 8 - #8                   |


|  |        |
|--|--------|
| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |        |
| 6-15-10                                      |        |
| REVISIONS                                    |        |
| DATE   | CHANGE |
|  |        |

This document was originally issued and sealed by Terrence R. Udland Registration Number PE- 2674 , on 6/15/10 and the original document is stored at the North Dakota Department of Transportation




CONTROLLER CABINET FOUNDATION PAD MOUNT

The Controller Cabinet Foundation shall be bid as Concrete Foundation - Traffic Signals.




TRANSFORMER & FEED POINT  
CABINET FOUNDATION PAD MOUNT

The Transformer & Feed Point Cabinet Foundation Pad Mount shall be bid as Concrete Foundation ~ Feed Point ~ Type A.





The Working Area Slab shall be installed where shown on the plans and shall not be bid separately but shall be included in the price bid for Concrete Foundation - Traffic Signals.





FEED POINT CABINET  
FOUNDATION PAD MOUNT

The Feed Point Cabinet Foundation Pad Mount shall be bid as Concrete Foundation ~ Feed Point ~ Type B.




LIGHT & SIGNAL STANDARD FOUNDATION




Alternate Signal Standard Base


For use only with Type V, VI, and VII signal standards.



Type II





Type V, VI, VII



Side View

Front View

Pedestrian Push Button Post Details (A)




Anchor Bolt Detail

- (A) Use positioning of the sign, pushbutton, and direction of arrow to clearly indicate which crosswalk is actuated by the push button. Place type of sign based on the jurisdiction in which placed.
- (B) Attach sign to post using rust resistant 0.081 aluminum bracket and banding. See Standard Signs book for dimensions and legend series. See plans for type of sign.

Notes:

- Signal Heads: See traffic signal layout for correct mounting position, number, size, and arrangement of lenses.
- Steel Standards: Place signal standard a minimum of 3 ft. from the face of the curb to center of signal standard, unless shown otherwise on layout sheets.
- Paint: See note sheet for required color of paint.
- Transformer Base: In lieu of transformer base use alternate signal standard base.



Signal Standard Minimum Clearance Details

| NORTH DAKOTA<br>DEPARTMENT OF TRANSPORTATION |   |
|--|---|
| 11-14-13                                     |   |
| REVISIONS                                    |   |
| DATE   | CHANGE  |
| 10-17-17<br>10-25-19                         | Updated to active voice.<br>Added 10" dim for ped pushbutton. |

This document was originally issued and sealed by  
Kirk J Hoff,  
Registration Number  
PE- 4683,  
on 10/25/19 and the original document is stored at the  
North Dakota Department  
of Transportation